

## REPORT DOCUMENTATION PAGE

Form Approved  
OPM No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)

2. REPORT DATE

3. REPORT TYPE AND DATES COVERED

Final 4 Feb. 1990 to 4 Feb. 1991

4. TITLE AND SUBTITLE Ada Compiler Validation Summary Report: SD-Scicon plc, XD Ada MC68000 V1.0-09, VAX Cluster (Host) to MC68000 (Target), 900204N1.10252

5. FUNDING NUMBERS

6. AUTHOR(S)

National Computing Centre Limited  
Manchester, UNITED KINGDOM

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

National Computing Centre Limited  
Oxford Road  
Manchester M1 7ED  
UNITED KINGDOM8. PERFORMING ORGANIZATION  
REPORT NUMBER

AVF-VSR-90502/66

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Ada Joint Program Office  
United States Department of Defense  
Washington, D.C. 20301-3081SPONSORING/MONITORING AGENCY  
REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

SD-Scicon plc, XD Ada MC68000 V1.0-09, Manchester, England, VAX Cluster (Comprising of a VAX 8600 and 7 MicroVAX II's) under VMS 5.1 (Host) to MC68000 processor running on an MVME117-3FP MPU VME module using a MC68881 floating point peripheral (bare machine), ACVC 1.10.

14. SUBJECT TERMS Ada programming language, Ada Compiler Validation Summary Report, Ada Compiler Validation Capability, Validation Testing, Ada Validation Office, Ada Validation Facility, ANSI/MIL-STD-1815A, Ada Joint Program Office

15. NUMBER OF PAGES

16. PRICE CODE

17. SECURITY CLASSIFICATION  
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION  
OF THIS PAGE

UNCLASSIFIED

19. SECURITY CLASSIFICATION  
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

AVF Control Number: AVF-VSR-90502/66

Ada COMPILER  
VALIDATION SUMMARY REPORT:  
Certificate Number: #900204N1.10252  
SD-Scicon plc  
XD Ada MC68000 V1.0-09  
VAX Cluster Host and MC68000 target



Completion of On-Site Testing:  
February 4 1990

Prepared By:  
Testing Services  
The National Computing Centre Limited  
Oxford Road  
Manchester M1 7ED  
England

Prepared For:  
Ada Joint Program Office  
United States Department of Defense  
Washington DC 20301-3081

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

Ada Compiler Validation Summary Report:

Compiler Name: XD Ada MC68000 V1.0-09

Certificate Number: #900204N1.10252

Host: VAX Cluster (Comprising of a VAX 8600 and 7 MicroVAX II's) under VMS 5.1

Target: MC68000 processor running on an MVME117-3FP MPU VME module using a MC68881 floating point peripheral (bare machine).

Testing Completed February 4 1990 Using ACVC 1.10

This report has been reviewed and is approved.

*J. Pink*

Jane Pink  
Testing Services Manager  
The National Computing Centre Limited  
Oxford Road  
Manchester M1 7ED  
England

*Dr. John F. Kramer*

Ada Validation Organization  
Dr. John F. Kramer  
Institute for Defense Analyses  
Alexandria VA 22311

*John P. Solomond*

Ada Joint Program Office  
Dr. John Solomond  
Director AJPO  
Department of Defense  
Washington DC 20301

---

**TABLE OF CONTENTS**

<b>CHAPTER 1</b>	
<b>INTRODUCTION</b>	<b>1</b>
1.1 <b>PURPOSE OF THIS VALIDATION SUMMARY REPORT</b>	<b>1</b>
1.2 <b>USE OF THIS VALIDATION SUMMARY REPORT</b>	<b>2</b>
1.3 <b>REFERENCES</b>	<b>2</b>
1.4 <b>DEFINITION OF TERMS</b>	<b>3</b>
1.5 <b>ACVC TEST CLASSES</b>	<b>4</b>
<b>CHAPTER 2</b>	
<b>CONFIGURATION INFORMATION</b>	<b>1</b>
2.1 <b>CONFIGURATION TESTED</b>	<b>1</b>
2.2 <b>IMPLEMENTATION CHARACTERISTICS</b>	<b>1</b>
<b>CHAPTER 3</b>	
<b>TEST INFORMATION</b>	<b>1</b>
3.1 <b>TEST RESULTS</b>	<b>1</b>
3.2 <b>SUMMARY OF TEST RESULTS BY CLASS</b>	<b>1</b>
3.3 <b>SUMMARY OF TEST RESULTS BY CHAPTER</b>	<b>1</b>
3.4 <b>WITHDRAWN TESTS</b>	<b>2</b>
3.5 <b>INAPPLICABLE TESTS</b>	<b>2</b>
3.6 <b>TEST, PROCESSING, AND EVALUATION MODIFICATIONS</b>	<b>5</b>
3.7 <b>ADDITIONAL TESTING INFORMATION</b>	<b>5</b>
<b>APPENDIX A</b>	
<b>DECLARATION OF CONFORMANCE</b>	<b>1</b>
<b>APPENDIX B</b>	
<b>APPENDIX F OF THE Ada STANDARD</b>	<b>1</b>
<b>APPENDIX C</b>	
<b>TEST PARAMETERS</b>	<b>1</b>
<b>APPENDIX D</b>	
<b>WITHDRAWN TESTS</b>	<b>1</b>

## CHAPTER 1

## INTRODUCTION

This Validation Summary Report (VSR) describes the extent to which a specific Ada compiler conforms to the Ada Standard, ANSI/MIL-STD-1815A. This report explains all technical terms used within it and thoroughly reports the results of testing this compiler using the Ada Compiler Validation Capability (ACVC). An Ada compiler must be implemented according to the Ada Standard, and any implementation-dependent features must conform to the requirements of the Ada Standard. The Ada Standard must be implemented in its entirety, and nothing can be implemented that is not in the Standard.

Even though all validated Ada compilers conform to the Ada Standard, it must be understood that some differences do exist between implementations. The Ada Standard permits some implementation dependencies -- for example, the maximum length of identifiers or the maximum values of integer types. Other differences between compilers result from the characteristics of particular operating systems, hardware, or implementation strategies. All the dependencies observed during the process of testing this compiler are given in this report.

The information in this report is derived from the test results produced during validation testing. The validation process includes submitting a suite of standardized tests, the ACVC, as inputs to an Ada compiler and evaluating the results. The purpose of validating is to ensure conformity of the compiler to the Ada Standard by testing that the compiler properly implements legal language constructs and that it identifies and rejects illegal language constructs. The testing also identifies behavior that is implementation dependent, but is permitted by the Ada Standard. Six classes of tests are used. These tests are designed to perform checks at compile time, at link time, and during execution.

### 1.1 PURPOSE OF THIS VALIDATION SUMMARY REPORT

This VSR documents the results of the validation testing performed on an Ada compiler. Testing was carried out for the following purposes:

- o To attempt to identify any language constructs supported by the compiler that do not conform to the Ada Standard
- o To attempt to identify any language constructs not supported by the compiler but required by the Ada Standard
- o To determine that the implementation-dependent behavior is allowed by the Ada Standard

Testing of this compiler was conducted by The National Computer Centre Limited according to procedures established by the Ada Joint Program Office and administered by the Ada Validation

Organization (AVO). On-site testing was completed on February 4 1990 at SD-SCICON plc, Pembroke House, Pembroke Broadway, Camberley, Surrey, GU15 3XD, UK.

## **1.2 USE OF THIS VALIDATION SUMMARY REPORT**

Consistent with the national laws of the originating country, the AVO may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject compiler has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from:

**Ada Information Clearinghouse  
Ada Joint Program Office  
OUSDRE  
The Pentagon, Rm 3D-139 (Fern Street)  
Washington DC 20301-3081**

or from:

**Testing Services  
The National Computing Centre Limited  
Oxford Road  
Manchester M1 7ED  
England**

Questions regarding this report or the validation test results should be directed to the AVF listed above or to:

**Ada Validation Organization  
Institute for Defense Analyses  
1801 North Beauregard Street  
Alexandria VA 22311**

## **1.3 REFERENCES**

1. Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
2. Ada Compiler Validation Procedures and Guidelines, Ada Joint Program Office, 1 January 1987.

3. Ada Compiler Validation Capability Implementers' Guide, SofTech, Inc., December 1986.
4. Ada Compiler Validation Capability User's Guide, December 1986.

#### 1.4 DEFINITION OF TERMS

ACVC	The Ada Compiler Validation Capability. The set of Ada programs that tests the conformity of an Ada compiler to the Ada programming language.
Ada Commentary	An Ada Commentary contains all information relevant to the point addressed by a comment on the Ada Standard. These comments are given a unique identification number having the form AI-ddddd.
Ada Standard	ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
Applicant	The agency requesting validation.
AVF	The Ada Validation Facility. The AVF is responsible for conducting compiler validations according to procedures contained in the <u>Ada Compiler Validation Procedures and Guidelines</u> .
AVO	The Ada Validation Organization. The AVO has oversight authority over all AVF practices for the purpose of maintaining a uniform process for validation of Ada compilers. The AVO provides administrative and technical support for Ada validations to ensure consistent practices.
Compiler	A processor for the Ada language. In the context of this report, a compiler is any language processor, including cross-compilers, translators, and interpreters.
Failed test	An ACVC test for which the compiler generates a result that demonstrates nonconformity to the Ada Standard.
Host	The computer on which the compiler resides.
Inapplicable test	An ACVC test that uses features of the language that a compiler is not required to support or may legitimately support in a way other than the one expected by the test.
Passed test	An ACVC test for which a compiler generates the expected result.

---

Target	The computer which executes the code generated by the compiler.
Test	A program that checks a compiler's conformity regarding a particular feature or a combination of features to the Ada Standard. In the context of this report, the term is used to designate a single test, which may comprise one or more files.
Withdrawn test	An ACVC test found to be incorrect and not used to check conformity to the Ada Standard. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains illegal or erroneous use of the language.

### 1.5 ACVC TEST CLASSES

Conformity to the Ada Standard is measured using the ACVC. The ACVC contains both legal and illegal Ada programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable, and special program units are used to report their results during execution. Class B tests are expected to produce compilation errors. Class L tests are expected to produce errors because of the way in which a program library is used at link time.

Class A tests ensure the successful compilation and execution of legal Ada programs with certain language constructs which cannot be verified at run time. There are no explicit program components in a Class A test to check semantics. For example, a Class A test checks that reserved words of another language (other than those already reserved in the Ada language) are not treated as reserved words by an Ada compiler. A Class A test is passed if no errors are detected at compile time and the program executes to produce a PASSED message.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that every syntax or semantic error in the test is detected. A Class B test is passed if every illegal construct that it contains is detected by the compiler.

Class C tests check the run time system to ensure that legal Ada programs can be correctly compiled and executed. Each Class C test is self-checking and produces a PASSED, FAILED, or NOT APPLICABLE message indicating the result when it is executed.

Class D tests check the compilation and execution capacities of a compiler. Since there are no capacity requirements placed on a compiler by the Ada Standard for some parameters -- for example, the number of identifiers permitted in a compilation or the number of units in a library - a compiler may refuse to compile a Class D test and still be a conforming compiler. Therefore, if a Class D test fails to compile because the capacity of the compiler is exceeded, the test is classified as inapplicable. If a Class D test compiles successfully, it is self-checking and produces a PASSED or FAILED message during execution.



Class E tests are expected to execute successfully and check implementation-dependent options and resolutions of ambiguities in the Ada Standard. Each Class E test is self-checking and produces a NOT APPLICABLE, PASSED, or FAILED message when it is compiled and executed. However, the Ada Standard permits an implementation to reject programs containing some features addressed by Class E tests during compilation. Therefore, a Class E test is passed by a compiler if it is compiled successfully and executes to produce a PASSED message, or if it is rejected by the compiler for an allowable reason.

Class L tests check that incomplete or illegal Ada programs involving multiple, separately compiled units are detected and not allowed to execute. Class L tests are compiled separately and execution is attempted. A Class L test passes if it is rejected at link time -- that is, an attempt to execute the main program must generate an error message before any declarations in the main program or any units referenced by the main program are elaborated. In some cases, an implementation may legitimately detect errors during compilation of the test.

Two library units, the package REPORT and the procedure CHECK\_FILE, support the self-checking features of the executable tests. The package REPORT provides the mechanism by which executable tests report PASSED, FAILED, or NOT APPLICABLE results. It also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The procedure CHECK\_FILE is used to check the contents of text files written by some of the Class C tests for Chapter 14 of the Ada Standard. The operation of REPORT and CHECK\_FILE is checked by a set of executable tests. These tests produce messages that are examined to verify that the units are operating correctly. If these units are not operating correctly, then the validation is not attempted.

The text of each test in the ACVC follows conventions that are intended to ensure that the tests are reasonably portable without modification. For example, the tests make use of only the basic set of 55 characters, contain lines with a maximum length of 72 characters, use small numeric values, and place features that may not be supported by all implementations in separate tests. However, some tests contain values that require the test to be customized according to implementation-specific values -- for example, an illegal file name. A list of the values used for this validation is provided in Appendix C.

A compiler must correctly process each of the tests in the suite and demonstrate conformity to the Ada Standard by either meeting the pass criteria given for the test or by showing that the test is inapplicable to the implementation. The applicability of a test to an implementation is considered each time the implementation is validated. A test that is inapplicable for one validation is not necessarily inapplicable for a subsequent validation. Any test that was determined to contain an illegal language construct or an erroneous language construct is withdrawn from the ACVC and, therefore, is not used in testing a compiler. The tests withdrawn at the time of this validation are given in Appendix D.

CHAPTER 2

CONFIGURATION INFORMATION

**2.1 CONFIGURATION TESTED**

The candidate compilation system for this validation was tested under the following configuration:

Compiler: XD Ada MC68000 V1.0-09

ACVC Version: 1.10

Certificate Number: #900204N1.10252

Host Computer:

Machine: VAX Cluster (comprising of a VAX 8600 and 7 MicroVAX II's)

Operating System: VMS 5.1

Memory Size: VAX 8600 - 20Mbytes  
MicroVAX II's - 1 x 16 Mbytes  
6 x 9 Mbytes

Target Computer:

Machine: MC68000 processor running on an MVME117-3FP MPU VME module using an MC68881 floating point peripheral.

Operating System Bare machine.

Memory Size: 512Kb

Communications Network: RS232 link

**2.2 IMPLEMENTATION CHARACTERISTICS**

One of the purposes of validating compilers is to determine the behavior of a compiler in those areas of the Ada Standard that permit implementations to differ. Class D and E tests specifically check for such implementation differences. However, tests in other classes also characterize an implementation. The tests demonstrate the following characteristics:

a. Capacities.

- (1) The compiler correctly processes a compilation containing 723 variables in the same declarative part. (See test D29002K.)
- (2) The compiler correctly processes tests containing loop statements nested to 65 levels. (See tests D55A03A..H (8 tests).)
- (3) The compiler correctly processes tests containing block statements nested to 65 levels. (See test D56001B.)
- (4) The compiler correctly processes tests containing recursive procedures separately compiled as subunits nested to 17 levels. (See tests D64005E..G (3 tests).)

b. Predefined types.

- (1) This implementation supports the additional predefined types `SHORT_INTEGER`, `SHORT_SHORT_INTEGER`, `LONG_FLOAT`, and `LONG_LONG_FLOAT`, in the package `STANDARD`. (See tests B86001T..Z (7 tests).)

c. Expression evaluation.

The order in which expressions are evaluated and the time at which constraints are checked are not defined by the language. While the ACVC tests do not specifically attempt to determine the order of evaluation of expressions, test results indicate the following:

- (1) None of the default initialization expressions for record components are evaluated before any value is checked for membership in a component's subtype. (See test C32117A.)
- (2) Assignments for subtypes are performed with the same precision as the base type. (See test C35712B).
- (3) This implementation uses no extra bits for extra precision and uses all extra bits for extra range. (See test C35903A.)
- (4) `NUMERIC_ERROR` is raised when an integer literal operand in a comparison or membership test is outside the range of the base type. (See test C45232A.)
- (5) `NUMERIC_ERROR` is raised when a literal operand in a fixed-point comparison or membership test is outside the range of the base type. (See test C45252A.)
- (6) Underflow is gradual. (See tests C45524A..Z (26 tests).)

d. Rounding.

The method by which values are rounded in type conversions is not defined by the language. While the ACVC tests do not specifically attempt to determine the method of rounding, the test results indicate the following:

- (1) The method used for rounding to integer is round to even. (See tests C46012A..Z (26 tests).)
- (2) The method used for rounding to longest integer is round to even. See tests C46012A..Z (26 tests).)
- (3) The method used for rounding to integer in static universal real expressions is round away from zero. (See test C4A014A.)

e. Array types.

An implementation is allowed to raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` for an array having a 'LENGTH that exceeds `STANDARD.INTEGER'LAST` and/or `SYSTEM.MAX_INT`. For this implementation:

- (1) Declaration of an array type or subtype declaration with more than `SYSTEM.MAX_INT` components raises `NUMERIC_ERROR`. (See test C36003A.)
- (2) `NUMERIC_ERROR` is raised when an array type with `INTEGER'LAST + 2` components is declared. (See test C36202A.)
- (3) `NUMERIC_ERROR` is raised when an array type with `SYSTEM.MAX_INT + 2` components is declared. (See test C36202B.)
- (4) A packed `BOOLEAN` array having a 'LENGTH exceeding `INTEGER'LAST` raises `NUMERIC_ERROR` when the array type is declared. (See test C52103X.)
- (5) A packed two-dimensional `BOOLEAN` array with more than `INTEGER'LAST` components `NUMERIC_ERROR` when the array type is declared. (See test C52104Y.)
- (6) In assigning one-dimensional array types, the expression is evaluated in its entirety before `CONSTRAINT_ERROR` is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)
- (7) In assigning two-dimensional array types, the expression is not evaluated in its entirety before `CONSTRAINT_ERROR` is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- f. A null array with one dimension of length greater than INTEGER'LAST may raise NUMERIC\_ERROR or CONSTRAINT\_ERROR either when declared or assigned. Alternatively, an implementation may accept the declaration. However, lengths must match in array slice assignments. This implementation raises no exception. (See test E52103Y.)
- g. Discriminated types.
  - (1) In assigning record types with discriminants, the expression is evaluated in its entirety before CONSTRAINT\_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)
- h. Aggregates.
  - (1) In the evaluation of a multi-dimensional aggregate, the test results indicate that all choices are evaluated before checking against the index type. (See tests C43207A and C43207B.)
  - (2) In the evaluation of an aggregate containing subaggregates, all choices are evaluated before being checked for identical bounds. (See test E43212B.)
  - (3) CONSTRAINT\_ERROR is raised after all choices are evaluated when a bound in a non-null range of a non-null aggregate does not belong to an index subtype. (See test E43211B.)
- i. Pragmas.
  - (1) The pragma INLINE is supported for functions or procedures. (See tests LA3004A..B (2 tests), EA3004C..D (2 tests), and CA3004E..F (2 tests).)
- j. Generics.
  - (1) Generic specifications and bodies can be compiled in separate compilations. (See tests CA1012A, CA2009C, CA2009F, BC3204C, and BC3205D.)
  - (2) Generic subprogram declarations and bodies can be compiled in separate compilations. (See tests CA1012A and CA2009F.)
  - (3) Generic library subprogram specifications and bodies can be compiled in separate compilations. (See test CA1012A.)
  - (4) Generic non-library package bodies as subunits can be compiled in separate compilations. (See test CA2009C.)

- (5) Generic non-library subprogram bodies can be compiled in separate compilations from their stubs. (See test CA2009F.)
  - (6) Generic unit bodies and their subunits can be compiled in separate compilations. (See test CA3011A.)
  - (7) Generic package declarations and bodies can be compiled in separate compilations. (See tests CA2009C, BC3204C, and BC3205D.)
  - (8) Generic library package specifications and bodies can be compiled in separate compilations. (See tests BC3204C and BC3205D.)
- k. Input and output.
- (1) The package SEQUENTIAL\_IO can be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101C, EE2201D, and EE2201E.)
  - (2) The package DIRECT\_IO can be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101H, EE2401D, and EE2401G.)
  - (3) The director, AJPO, has determined (AI-00332) that every call to OPEN and CREATE must raise USE\_ERROR or NAME\_ERROR if file input/output is not supported. This implementation exhibits this behavior for SEQUENTIAL\_IO, DIRECT\_IO, and TEXT\_IO.

## CHAPTER 3

## TEST INFORMATION

**3.1 TEST RESULTS**

Version 1.10 of the ACVC comprises 3717 tests. When this compiler was tested, 44 tests had been withdrawn because of test errors. The AVF determined that 504 tests were inapplicable to this implementation. All inapplicable tests were processed during validation testing except for 159 executable tests that use floating-point precision exceeding that supported by the implementation. Modifications to the code, processing, or grading for 16 tests were required to successfully demonstrate the test objective. (See section 3.6.)

The AVF concludes that the testing results demonstrate acceptable conformity to the Ada Standard.

**3.2 SUMMARY OF TEST RESULTS BY CLASS**

RESULT	TEST CLASS						TOTAL
	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>	<u>L</u>	
Passed	129	1133	1828	17	16	46	3169
Inapplicable	0	5	487	0	12	0	504
Withdrawn	1	2	35	0	6	0	44
TOTAL	130	1140	2350	17	34	46	3717

**3.3 SUMMARY OF TEST RESULTS BY CHAPTER**

RESULT	CHAPTER														TOTAL
	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>	<u>7</u>	<u>8</u>	<u>9</u>	<u>10</u>	<u>11</u>	<u>12</u>	<u>13</u>	<u>14</u>		
Passed	201	592	567	245	172	99	162	331	137	36	252	295	78	3169	
Inapp	11	57	111	3	0	0	4	1	0	0	0	74	243	504	
Withdrawn	1	1	0	0	0	0	0	2	0	0	1	35	4	44	
TOTAL	213	650	680	248	172	99	166	334	137	36	253	404	325	3717	

### 3.4 WITHDRAWN TESTS

The following 44 tests were withdrawn from ACVC Version 1.10 at the time of this validation:

E28005C	A39005G	B97102E
C97116A	BC3009B	CD2A62D
CD2A63A..D (4 tests)	CD2A66A..D (4 tests)	CD2A73A..D (4 tests)
CD2A76A..D (4 tests)	CD2A81G	CD2A83G
CD2A84M..N (2 tests)	CD2B15C	CD2D11B
CD5007B	CD5011O	ED7004B
ED7005C..D (2 tests)	ED7006C..D (2 tests)	CD7105A
CD7203B	CD7204B	CD7205C
CD7205D	CE2107I	CE3111C
CE3301A	CE3411B	

See Appendix D for the reason that each of these tests was withdrawn.

### 3.5 INAPPLICABLE TESTS

Some tests do not apply to all compilers because they make use of features that a compiler is not required by the Ada Standard to support. Others may depend on the result of another test that is either inapplicable or withdrawn. The applicability of a test to an implementation is considered each time a validation is attempted. A test that is inapplicable for one validation attempt is not necessarily inapplicable for a subsequent attempt. For this validation attempt, 504 tests were inapplicable for the reasons indicated:

- a. The following 159 tests are not applicable because they have floating-point type declarations requiring more digits than SYSTEM.MAX\_DIGITS:

C24113O..Y (11 tests)	C35705O..Y (11 tests)	C35706O..Y (11 tests)
C35707O..Y (11 tests)	C35708O..Y (11 tests)	C35802O..Z (12 tests)
C45241O..Y (11 tests)	C45321O..Y (11 tests)	C45421O..Y (11 tests)
C45521O..Z (12 tests)	C45524O..Z (12 tests)	C45621O..Z (12 tests)
C45641O..Y (11 tests)	C46012O..Z (12 tests)	

- b. C35702A and B86001T are not applicable because this implementation supports no predefined type SHORT\_FLOAT.

- c. The following 16 tests are not applicable because this implementation does not support a predefined type LONG\_INTEGER:

C45231C	C45304C	C45502C	C45503C	C45504C
C45504F	C45611C	C45613C	C45614C	C45631C
C45632C	B52004D	C55B07A	B55B09C	
B86001W	CD7101F			



- 
- d. C45531M..P (4 tests) and C45532M..P (4 tests) are all inapplicable because this implementation has a 'MAX\_MANTISSA of 31 and these tests require the compiler to support a greater value.
  - e. C86001F is not applicable because, for this implementation, the package TEXT\_IO is dependent upon package SYSTEM. This test recompiles package SYSTEM, making package TEXT\_IO, and hence package REPORT, obsolete.
  - f. B86001Y is not applicable because this implementation supports no predefined fixed-point type other than DURATION.
  - g. C96005B is not applicable because there are no values of type DURATION'BASE that are outside the range of DURATION.
  - h. CD1009C, CD2A41A..B (2 tests), CD2A41E and CD2A42A..J (10 tests) are not applicable because 'SIZE representation clauses for floating-point types are not supported.
  - i. CD1C04C is inapplicable because this implementation does not support model numbers of a derived type that are not representable values of the parent type.
  - j. CD2A52C..D (2 tests), CD2A52G..H (2 tests), CD2A54C..D (2 tests) and CD2A54H are not applicable because for this implementation the legality of a 'SIZE clause for a derived fixed point type can depend on the representation chosen for the parent type.
  - k. CD2A53C, and CD2A54G are not applicable because within these tests the SMALL specified for a derived fixed point is finer than the SMALL for the parent type. As a result some model numbers of the derived type are not representable values of the parent type which this implementation does not allow.
  - l. The following 23 tests are not applicable because this implementation does not support packing by means of a length clause for an array type:
 

CD2A61A..L (12 tests)	CD2A62A..C (3 tests)	CD2A64A..D (4 tests)
CD2A65A..D (4 tests)		
  - m. The following 16 tests are not applicable because this implementation does not support packing by means of a length clause for a record type:
 

CD2A71A..D (4 tests)	CD2A72A..D (4 tests)	CD2A74A..D (4 tests)
CD2A75A..D (4 tests)		
  - n. CD2A84B..I (8 tests) and CD2A84K..L (2 tests) are not applicable because this implementation only accepts length clause for access types, if the default size (32 bits) is specified. These tests specify sizes other than 32 bits.

- o. The following 241 tests are inapplicable because sequential, text, and direct access files are not supported:

CE2102A..C (3 tests)	CE2102G..H (2 tests)	CE2102K
CE2102N..Y (12 tests)	CE2103C..D (2 tests)	CE2104A..D (4 tests)
CE2105A..B (2 tests)	CE2106A..B (2 tests)	CE2107A..H (8 tests)
CE2107L	CE2108A..H (8 tests)	CE2109A..C (3 tests)
CE2110A..D (4 tests)	CE2111A..I (9 tests)	CE2115A..B (2 tests)
CE2201A..C (3 tests)	EE2201D..E (2 tests)	CE2201F..N (9 tests)
CE2204A..D (4 tests)	CE2205A	CE2208B
CE2401A..C (3 tests)	EE2401D	CE2401E..F (2 tests)
EE2401G	CE2401H..L (5 tests)	CE2404A..B (2 tests)
CE2405B	CE2406A	CE2407A..B (2 tests)
CE2408A..B (2 tests)	CE2409A..B (2 tests)	CE2410A..B (2 tests)
CE2411A	CE3102A..B (2 tests)	EE3102C
CE3102F..H (3 tests)	CE3102J..K (2 tests)	CE3103A
CE3104A..C (3 tests)	CE3107B	CE3108A..B (2 tests)
CE3109A	CE3110A	CE3111A..B (2 tests)
CE3111D..E (2 tests)	CE3112A..D (4 tests)	CE3114A..B (2 tests)
CE3115A	EE3203A	CE3208A
EE3301B	CE3302A	CE3305A
CE3402A	EE3402B	CE3402C..D (2 tests)
CE3403A..C (3 tests)	CE3403E..F (2 tests)	CE3404B..D (3 tests)
CE3405A	EE3405B	CE3405C..D (2 tests)
CE3406A..D (4 tests)	CE3407A..C (3 tests)	CE3408A..C (3 tests)
CE3409A	CE3409C..E (3 tests)	EE3409F
CE3410A	CE3410C..E (3 tests)	EE3410F
CE3411A	CE3411C	CE3412A
CE3413A	CE3413C	CE3602A..D (4 tests)
CE3603A	CE3604A..B (2 tests)	CE3605A..E (5 tests)
CE3606A..B (2 tests)	CE3704A..F (6 tests)	CE3704M..O (3 tests)
CE3706D	CE3706F..G (2 tests)	CE3804A..P (16 tests)
CE3805A..B (2 tests)	CE3806A..B (2 tests)	CE3806D..E (2 tests)
CE3806G..H (2 tests)	CE3905A..C (3 tests)	CE3905L
CE3906A..C (3 tests)	CE3906E..F (2 tests)	

- p. CE3901A is not applicable because this implementation raises NAME\_ERROR if a filename parameter to TEXT\_IO.CREATE is non-null. This test assumes that USE\_ERROR will be raised.
- q. EE3412C is not applicable for this implementation because their implementation of the body of the package report does not use TEXT\_IO.

---

### 3.6 TEST, PROCESSING, AND EVALUATION MODIFICATIONS

It is expected that some tests will require modifications of code, processing, or evaluation in order to compensate for legitimate implementation behaviour. Modifications are made by the AVF in cases where legitimate implementation behaviour prevents the successful completion of an (otherwise) applicable test. Examples of such modifications include: adding a length clause to alter the default size of a collection; splitting a Class B test into subtests so that all errors are detected; and confirming that messages produced by an executable test demonstrate conforming behaviour that was not anticipated by the test (such as raising one exception instead of another).

Modifications were required for 16 tests.

C34006D is classified as passed if the test fails with messages "INCORRECT TYPE SIZE" or "INCORRECT OBJECT SIZE". This test incorrectly assumes that the space allocated for objects must be less than or equal to the minimum needed by the (sub) type. This is not true for this implementation.

C4524A..N (14 tests) were modified because these tests expect that the result of continued division of a real number will be zero; the Ada Standard, however, only requires that the result be within the type's `SAFE_SMALL` of zero. Thus, these tests were modified to include a check that the result was in the smallest positive safe interval for the type. The implementation passed the modified tests. Each test was modified by inserting the following code after line 138;

The following test was split because syntax errors at one point resulted in the compiler not detecting other errors in the test:

B97103E

### 3.7 ADDITIONAL TESTING INFORMATION

#### 3.7.1 Prevalidation

Prior to validation, a set of test results for ACVC Version 1.10 produced by the **XD Ada MC68000 V1.0-09** compiler was submitted to the AVF by the applicant for review. Analysis of these results demonstrated that the compiler successfully passed all applicable tests, and the compiler exhibited the expected behaviour on all inapplicable tests.

#### 3.7.2 Test Method

Testing of the **XD Ada MC68000 V1.0-09** compiler using ACVC Version 1.10 was conducted on-site by a validation team from the AVF. The configuration in which the testing was performed is described by the following designations of hardware and software components:

---

Host computer	: VAX Cluster (comprising of a VAX 8600 and 7 MicroVAX II's)
Host operating system	: VMS 5.1
Target computer	: MC68000 processor running on the MVME117-3FP MPU VME module using an MC68881 floating point peripheral.
Compiler	: XD Ada MC68000 V1.0-09
Assembler	: XD Ada MC68000 V1.0-09
Linker	: XD Ada MC68030 V1.0-04
Loader	: XD Ada MC68000 S1.0-10
Downloader	: XD Ada MC68030 V1.0-04
Runtime System	: XD Ada MC68000 V1.0-09

The host and target computers were linked via a RS232 link.

A magnetic tape containing all tests except for withdrawn tests and tests requiring unsupported floating-point precisions was taken on-site by the validation team for processing. Tests that make use of implementation-specific values were customized before being written to the magnetic tape. Tests requiring modifications during the prevalidation testing were not included in their modified form on the magnetic tape.

The contents of the magnetic tape were loaded directly onto the host computer.

After the test files were loaded to disk, the full set of tests was compiled and linked on the VAX Cluster, then all executable images were transferred to the MC68000 target via the RS232 link and run. Results were printed from the host computer.

The compiler was tested using command scripts provided by SD-Scicon plc and reviewed by the validation team. The compiler was tested using all the following option settings. Details of these settings are given at the end of Appendix B.

Tests were compiled, linked, and executed (as appropriate) using 8 computers and two target computers. Test output, compilation listings, and job logs were captured on magnetic media and archived at the AVF. The listings examined on-site by the validation team were also archived.

### 3.7.3 Test Site

Testing was conducted at SD-Scicon plc, Pembroke House, Pembroke Broadway, Camberley, Surrey, GU15 3XD, UK and was completed on February 4 1990.

## DECLARATION OF CONFORMANCE

---

### APPENDIX A

#### DECLARATION OF CONFORMANCE

SD-Scicon plc has submitted the following Declaration of Conformance concerning the XD Ada MC68000 V1.0-09 compiler.

DECLARATION OF CONFORMANCE

---

DECLARATION OF CONFORMANCE

Compiler Implementor: SD-Scicon plc  
Ada Validation Facility: The National Computing Centre Limited  
Oxford Road  
Manchester  
M1 7ED


Ada Compiler Validation Capability (ACVC) Version: 1.10

Base Configuration

Base Compiler Name: XD Ada MC68000 V1.0-09  
Host Architecture: VAX Cluster (comprising of a VAX 8600 and 7  
MicroVAX II's)  
Host OS and Version: VMS 5.1  
Target Architecture: MC68000 processor on an MVME117-3FP MPU  
VME module using an MC68881 floating point  
peripheral (bare machine).

Implementor's Declaration

I, the undersigned, representing SD-Scicon plc, have implemented no deliberate extensions to the Ada Language Standard ANSI/MIL-STD-1815A in the compiler(s) listed in this declaration. I declare that SD-Scicon plc is the owner of record of the Ada language compiler(s) listed above and, as such, is responsible for maintaining said compiler(s) in conformance to ANSI/MIL-STD-1815A. All certificates and registrations for Ada language compiler(s) listed in this declaration shall be made only in the owner's corporate name.

  
\_\_\_\_\_

Date : 25 April 90

Bill Davison  
WORLDWIDE CUSTOMER SERVICES MANAGER

## DECLARATION OF CONFORMANCE

---

### Owner's Declaration

I, the undersigned, representing SD-Scicon plc, take full responsibility for implementation and maintenance of the Ada compiler(s) listed above, and agree to the public disclosure of the final Validation Summary Report. I declare that all of the Ada language compilers listed, and their host/target performance, are in compliance with the Ada Language Standard ANSI/MIL-STD-1815A.



Date : 15 April 90

**Bill Davison**  
**WORLDWIDE CUSTOMER SERVICES MANAGER**

## APPENDIX B

## APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in chapter 13 of the Ada Standard, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of the **XD Ada MC68000 V1.0-09** compiler, as described in this Appendix, are provided by **SD-Scicon plc**. Unless specifically noted otherwise, references in this appendix are to compiler documentation and not to this report. Implementation-specific portions of the package STANDARD, which are not a part of Appendix F, are:

package STANDARD is

...

type INTEGER is range -2147483648 .. 2147483647;

type SHORT\_INTEGER is range -32768 .. 32767;

type SHORT\_SHORT\_INTEGER is range -128 .. 127;

type FLOAT is digits 6 range  $-(2^{128} - 2^{104})$  ..

$2^{128} - 2^{104}$ ;

type LONG\_FLOAT is digits 15 range  $-(2^{1024} - 2^{971})$  ..

$2^{1024} - 2^{971}$ ;

type LONG\_LONG\_FLOAT is digits 18 range  $-(2^{16384} - 2^{16320})$  ..

$2^{16384} - 2^{16320}$

type DURATION is delta 1.E-4 range -131072.0000 .. 131071.9999;

...

end STANDARD;



## Implementation-Dependent Characteristics

---

---

### F.3 Specification of Package System

The package SYSTEM for the MC68000 configuration differs from that of the standard MC68020 as follows:

---

#### F.3.1 Changes to Package SYSTEM for the MC68000 Target

```
type NAME is (MC68000);  
SYSTEM_NAME : constant NAME := MC68000;  
STORAGE_UNIT : constant := 8;  
MEMORY_SIZE : constant := 2**24;  
TICK : constant := 2#1.0#E-10;  
type ADDRESS_INT is range 0 .. MEMORY_SIZE-1;  
for ADDRESS_INT'SIZE use 32;
```

---

## **F.6 Interpretation of Expressions Appearing in Address Clauses**

For address clauses on variables, the address expression is interpreted as a Motorola 24-bit address.

In XD Ada for MC68000, values of type `SYSTEM.ADDRESS` are interpreted as integers in the range  $0 \dots 2^{24} - 1$ .

# Implementation-Dependent Characteristics

---

## NOTE

This appendix is not part of the standard definition of the Ada programming language.

This appendix summarizes the following implementation-dependent characteristics of XD Ada:

- Listing the XD Ada pragmas and attributes.
- Giving the specification of the package SYSTEM.
- Presenting the restrictions on representation clauses and unchecked type conversions.
- Giving the conventions for names denoting implementation-dependent components in record representation clauses.
- Giving the interpretation of expressions in address clauses.
- Presenting the implementation-dependent characteristics of the input-output packages.
- Presenting other implementation-dependent characteristics.

---

## F.1 Implementation-Dependent Pragmas

XD Ada provides the following pragmas, which are defined elsewhere in the text. In addition, XD Ada restricts the predefined language pragmas `INLINE` and `INTERFACE`, provides pragma `VOLATILE` in addition to pragma `SHARED`, and provides pragma `SUPPRESS_ALL` in addition to pragma `SUPPRESS`. See Annex B for a descriptive pragma summary.

- `CALL_SEQUENCE_FUNCTION` (see Annex B)
- `CALL_SEQUENCE_PROCEDURE` (see Annex B)
- `EXPORT_EXCEPTION` (see Section 13.9a.3.2)
- `EXPORT_FUNCTION` (see Section 13.9a.1.2)
- `EXPORT_OBJECT` (see Section 13.9a.2.2)
- `EXPORT_PROCEDURE` (see Section 13.9a.1.2)
- `IMPORT_EXCEPTION` (see Section 13.9a.3.1)
- `IMPORT_FUNCTION` (see Section 13.9a.1.1)
- `IMPORT_OBJECT` (see Section 13.9a.2.1)
- `IMPORT_PROCEDURE` (see Section 13.9a.1.1)
- `LEVEL` (see Section 13.5.1)
- `LINK_OPTION` (see Annex B)
- `SUPPRESS_ALL` (see Section 11.7)
- `TITLE` (see Annex B)
- `VOLATILE` (see Section 9.11)

---

## F.2 Implementation-Dependent Attributes

XD Ada provides the following attributes, which are defined elsewhere in the text. See Appendix A for a descriptive attribute summary.

- `BIT` (see Section 13.7.2)
- `MACHINE_SIZE` (see Section 13.7.2)
- `TYPE_CLASS` (see Section 13.7a.2)

---

## F.3 Specification of the Package System

The package SYSTEM for the MC68020 is as follows:

---

### F.3.1 Package System for the MC68020 Target

**package** SYSTEM is

```
    type NAME is (MC68020);

    SYSTEM_NAME : constant NAME := MC68020;
    STORAGE_UNIT : constant := 8;
    MEMORY_SIZE : constant := 2**31-1;
    MIN_INT : constant := -(2**31);
    MAX_INT : constant := 2**31-1;
    MAX_DIGITS : constant := 18;
    MAX_MANTISSA : constant := 31;
    FINE_DELTA : constant := 2.0**(-31);
    TICK : constant := 162.5E-6;
    subtype PRIORITY is INTEGER range 0 .. 15;
    subtype LEVEL is INTEGER range 0 .. 7;

-- Address type
--
    type ADDRESS is private;

    ADDRESS_ZERO : constant ADDRESS;
    type ADDRESS_INT is range MIN_INT .. MAX_INT;
    function TO_ADDRESS (X : ADDRESS_INT) return ADDRESS;
    function TO_ADDRESS (X : {universal_integer}) return ADDRESS;
    function TO_ADDRESS_INT (X : ADDRESS) return ADDRESS_INT;

    function "+" (LEFT : ADDRESS; RIGHT : ADDRESS_INT) return ADDRESS;
    function "+" (LEFT : ADDRESS_INT; RIGHT : ADDRESS) return ADDRESS;
    function "-" (LEFT : ADDRESS; RIGHT : ADDRESS) return ADDRESS_INT;
    function "-" (LEFT : ADDRESS; RIGHT : ADDRESS_INT) return ADDRESS;

-- function "-" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
-- function "/=" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function "<" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function "<=" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function ">" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function ">=" (LEFT, RIGHT : ADDRESS) return BOOLEAN;

--
-- Note that because ADDRESS is a private type
-- the functions "-" and "/=" are already available
```

```

-- Generic functions used to access memory
--
generic
  type TARGET is private;
  function FETCH_FROM_ADDRESS (A : ADDRESS) return TARGET;

generic
  type TARGET is private;
  procedure ASSIGN_TO_ADDRESS (A : ADDRESS; T : TARGET);

type TYPE_CLASS is (TYPE_CLASS_ENUMERATION,
  TYPE_CLASS_INTEGER,
  TYPE_CLASS_FIXED_POINT,
  TYPE_CLASS_FLOATING_POINT,
  TYPE_CLASS_ARRAY,
  TYPE_CLASS_RECORD,
  TYPE_CLASS_ACCESS,
  TYPE_CLASS_TASK,
  TYPE_CLASS_ADDRESS);

--
-- XD Ada hardware-oriented types and functions
--
type BIT_ARRAY is array (INTEGER range <>) of BOOLEAN;
pragma PACK(BIT_ARRAY);
subtype BIT_ARRAY_8 is BIT_ARRAY (0 .. 7);
subtype BIT_ARRAY_16 is BIT_ARRAY (0 .. 15);
subtype BIT_ARRAY_32 is BIT_ARRAY (0 .. 31);
subtype BIT_ARRAY_64 is BIT_ARRAY (0 .. 63);
type UNSIGNED_BYTE is range 0 .. 255;
for UNSIGNED_BYTE'SIZE use 8;
function "not" (LEFT : UNSIGNED_BYTE) return UNSIGNED_BYTE;
function "and" (LEFT, RIGHT : UNSIGNED_BYTE) return UNSIGNED_BYTE;
function "or" (LEFT, RIGHT : UNSIGNED_BYTE) return UNSIGNED_BYTE;
function "xor" (LEFT, RIGHT : UNSIGNED_BYTE) return UNSIGNED_BYTE;

function TO_UNSIGNED_BYTE (X : BIT_ARRAY_8) return UNSIGNED_BYTE;
function TO_BIT_ARRAY_8 (X : UNSIGNED_BYTE) return BIT_ARRAY_8;

type UNSIGNED_BYTE_ARRAY is array (INTEGER range <>) of UNSIGNED_BYTE;

type UNSIGNED_WORD is range 0 .. 65535;
for UNSIGNED_WORD'SIZE use 16;
function "not" (LEFT : UNSIGNED_WORD) return UNSIGNED_WORD;
function "and" (LEFT, RIGHT : UNSIGNED_WORD) return UNSIGNED_WORD;
function "or" (LEFT, RIGHT : UNSIGNED_WORD) return UNSIGNED_WORD;
function "xor" (LEFT, RIGHT : UNSIGNED_WORD) return UNSIGNED_WORD;

function TO_UNSIGNED_WORD (X : BIT_ARRAY_16) return UNSIGNED_WORD;
function TO_BIT_ARRAY_16 (X : UNSIGNED_WORD) return BIT_ARRAY_16;

type UNSIGNED_WORD_ARRAY is array (INTEGER range <>) of UNSIGNED_WORD;

--
type UNSIGNED_LONGWORD is range MIN_INT .. MAX_INT;
for UNSIGNED_LONGWORD'SIZE use 32;

```

#### F-4 Implementation-Dependent Characteristics

```

function "not" (LEFT      : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;
function "and" (LEFT, RIGHT : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;
function "or"  (LEFT, RIGHT : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;
function "xor" (LEFT, RIGHT : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;

function TO_UNSIGNED_LONGWORD (X : BIT_ARRAY_32) return UNSIGNED_LONGWORD;
function TO_BIT_ARRAY_32      (X : UNSIGNED_WORD) return BIT_ARRAY_32;

type UNSIGNED_LONGWORD_ARRAY is array (INTEGER range <>) of UNSIGNED_LONGWORD;

-- Conventional names for static subtypes of type UNSIGNED_LONGWORD
--
subtype UNSIGNED_1  is UNSIGNED_LONGWORD range 0 .. 2** 1-1;
subtype UNSIGNED_2  is UNSIGNED_LONGWORD range 0 .. 2** 2-1;
subtype UNSIGNED_3  is UNSIGNED_LONGWORD range 0 .. 2** 3-1;
subtype UNSIGNED_4  is UNSIGNED_LONGWORD range 0 .. 2** 4-1;
subtype UNSIGNED_5  is UNSIGNED_LONGWORD range 0 .. 2** 5-1;
subtype UNSIGNED_6  is UNSIGNED_LONGWORD range 0 .. 2** 6-1;
subtype UNSIGNED_7  is UNSIGNED_LONGWORD range 0 .. 2** 7-1;
subtype UNSIGNED_8  is UNSIGNED_LONGWORD range 0 .. 2** 8-1;
subtype UNSIGNED_9  is UNSIGNED_LONGWORD range 0 .. 2** 9-1;
subtype UNSIGNED_10 is UNSIGNED_LONGWORD range 0 .. 2**10-1;
subtype UNSIGNED_11 is UNSIGNED_LONGWORD range 0 .. 2**11-1;
subtype UNSIGNED_12 is UNSIGNED_LONGWORD range 0 .. 2**12-1;
subtype UNSIGNED_13 is UNSIGNED_LONGWORD range 0 .. 2**13-1;
subtype UNSIGNED_14 is UNSIGNED_LONGWORD range 0 .. 2**14-1;
subtype UNSIGNED_15 is UNSIGNED_LONGWORD range 0 .. 2**15-1;
subtype UNSIGNED_16 is UNSIGNED_LONGWORD range 0 .. 2**16-1;
subtype UNSIGNED_17 is UNSIGNED_LONGWORD range 0 .. 2**17-1;
subtype UNSIGNED_18 is UNSIGNED_LONGWORD range 0 .. 2**18-1;
subtype UNSIGNED_19 is UNSIGNED_LONGWORD range 0 .. 2**19-1;
subtype UNSIGNED_20 is UNSIGNED_LONGWORD range 0 .. 2**20-1;
subtype UNSIGNED_21 is UNSIGNED_LONGWORD range 0 .. 2**21-1;
subtype UNSIGNED_22 is UNSIGNED_LONGWORD range 0 .. 2**22-1;
subtype UNSIGNED_23 is UNSIGNED_LONGWORD range 0 .. 2**23-1;
subtype UNSIGNED_24 is UNSIGNED_LONGWORD range 0 .. 2**24-1;
subtype UNSIGNED_25 is UNSIGNED_LONGWORD range 0 .. 2**25-1;
subtype UNSIGNED_26 is UNSIGNED_LONGWORD range 0 .. 2**26-1;
subtype UNSIGNED_27 is UNSIGNED_LONGWORD range 0 .. 2**27-1;
subtype UNSIGNED_28 is UNSIGNED_LONGWORD range 0 .. 2**28-1;
subtype UNSIGNED_29 is UNSIGNED_LONGWORD range 0 .. 2**29-1;
subtype UNSIGNED_30 is UNSIGNED_LONGWORD range 0 .. 2**30-1;
subtype UNSIGNED_31 is UNSIGNED_LONGWORD range 0 .. 2**31-1;

private
-- Not shown
end SYSTEM;

```

---

## **F.4 Restrictions on Representation Clauses**

The representation clauses allowed in XD Ada are length, enumeration, record representation, and address clauses.

In XD Ada, a representation clause for a generic formal type or a type that depends on a generic formal type is not allowed. In addition, a representation clause for a composite type that has a component or subcomponent of a generic formal type or a type derived from a generic formal type is not allowed.

Restrictions on length clauses are specified in Section 13.2; restrictions on enumeration representation clauses are specified in Section 13.3; and restrictions on record representation clauses are specified in Section 13.4.

---

## **F.5 Conventions for Implementation-Generated Names Denoting Implementation-Dependent Components in Record Representation Clauses**

XD Ada does not allocate implementation-dependent components in records.

---

## **F.6 Interpretation of Expressions Appearing in Address Clauses**

Expressions appearing in address clauses must be of the type ADDRESS defined in package SYSTEM (see Section 13.7a.1 and Section F.3).

XD Ada allows address clauses for variables (see Section 13.5). For address clauses on variables, the address expression is interpreted as a Motorola full 32-bit address.

XD Ada supports address clauses on task entries to allow interrupts to cause a *reschedule* directly. For address clauses on task entries, the address expression is interpreted as a Motorola exception vector offset.



In XD Ada for MC68020, values of type `SYSTEM.ADDRESS` are interpreted as integers in the range  $0 \dots 2^{32} - 1$ . As `SYSTEM.ADDRESS` is a private type, the only operations allowed on objects of this type are those given in package `SYSTEM`.

---

## F.7 Restrictions on Unchecked Type Conversions

XD Ada supports the generic function `UNCHECKED_CONVERSION` with the restrictions given in Section 13.10.2.

---

## F.8 Implementation-Dependent Characteristics of Input-Output Packages

The packages `SEQUENTIAL_IO` and `DIRECT_IO` are implemented as null packages that conform to the specification given in the *Reference Manual for the Ada Programming Language*. The packages raise the exceptions specified in Chapter 14 of the *Reference Manual for the Ada Programming Language*. The three possible exceptions that are raised by these packages are given here, in the order in which they are raised.

Exception	When Raised
<code>STATUS_ERROR</code>	Raised by an attempt to operate upon or close a file that is not open (no files can be opened).
<code>NAME_ERROR</code>	Raised if a file name is given with a call of <code>CREATE</code> or <code>OPEN</code> .
<code>USE_ERROR</code>	Raised if exception <code>STATUS_ERROR</code> is not raised.

`MODE_ERROR` cannot be raised since no file can be opened (therefore it cannot have a current mode).

The predefined package `LOW_LEVEL_IO` is not provided.

---

### F.8.1 The Package TEXT\_IO

The package TEXT\_IO conforms to the specification given in the *Reference Manual for the Ada Programming Language*. String input-output is implemented as defined. File input-output is supported to STANDARD\_INPUT and STANDARD\_OUTPUT only. The possible exceptions that are raised by package TEXT\_IO are as follows:

---

Exception	When Raised
STATUS_ERROR	Raised by an attempt to operate upon or close a file that is not open (no files can be opened).
NAME_ERROR	Raised if a file name is given with a call of CREATE or OPEN.
MODE_ERROR	Raised by an attempt to read from, or test for the end of, STANDARD_OUTPUT, or to write to STANDARD_INPUT.
END_ERROR	Raised by an attempt to read past the end of STANDARD_INPUT.
USE_ERROR	Raised when an unsupported operation is attempted, that would otherwise be legal.

---

The type COUNT is defined as follows:

```
type COUNT is range 0 .. INTEGER'LAST;
```

The subtype FIELD is defined as follows:

```
type FIELD is INTEGER range 0 .. 255;
```

---

### F.8.2 The Package IO\_EXCEPTIONS

The specification of the package IO\_EXCEPTIONS is the same as that given in the *Reference Manual for the Ada Programming Language*.

---

## F.9 Other Implementation Characteristics

Implementation characteristics associated with the definition of a main program, various numeric ranges, and implementation limits are summarized in the following sections.

---

### F.9.1 Definition of a Main Program

Any library procedure can be used as a main program provided that it has no formal parameters.

---

### F.9.2 Values of Integer Attributes

The ranges of values for integer types declared in package STANDARD are as follows:

SHORT_SHORT_INTEGER	$-2^7 \dots 2^7 - 1$	(-128 .. 127)
SHORT_INTEGER	$-2^{15} \dots 2^{15} - 1$	(-32768 .. 32767)
INTEGER	$-2^{31} \dots 2^{31} - 1$	(-2147483648 .. 2147483647)

For the package TEXT\_IO, the range of values for types COUNT and FIELD are as follows:

COUNT	$0 \dots 2^{31} - 1$	(0 .. 2147483647)
FIELD	$0 \dots 255$	

---

### F.9.3 Values of Floating-Point Attributes

Floating-point types are described in Section 3.5.7. The representation attributes of floating-point types are summarized in the following table:

	FLOAT	LONG_FLOAT	LONG_LONG_FLOAT
DIGITS	6	15	18
SIZE	32	64	96
MANTISSA	21	51	61
EMAX	84	204	244
EPSILON	$2^{-20}$	$2^{-50}$	$2^{-60}$
SMALL	$2^{-85}$	$2^{-205}$	$2^{-245}$
LARGE	$2^{84} - 2^{63}$	$2^{204} - 2^{153}$	$2^{244} - 2^{183}$
SAFE_EMAX	125	1021	16382
SAFE_SMALL	$2^{-126}$	$2^{-1022}$	$2^{-16383}$
SAFE_LARGE	$2^{125} - 2^{104}$	$2^{1021} - 2^{970}$	$2^{16382} - 2^{16321}$
FIRST	$-(2^{128} - 2^{104})$	$-(2^{1024} - 2^{971})$	$-(2^{16384} - 2^{16320})$
LAST	$2^{128} - 2^{104}$	$2^{1024} - 2^{971}$	$2^{16384} - 2^{16320}$
MACHINE_RADIX	2	2	2
MACHINE_MANTISSA	24	53	64
MACHINE_EMAX	128	1024	16384
MACHINE_EMIN	-125	-1021	-16382
MACHINE_ROUNDS	FALSE	FALSE	FALSE
MACHINE_OVERFLOWS	FALSE	FALSE	FALSE

#### F-10 Implementation-Dependent Characteristics

---

#### F.9.4 Attributes of Type DURATION

The values of the significant attributes of type DURATION are as follows:

DURATION'DELTA	1.E-4	( $10^{-4}$ )
DURATION'SMALL	2#1.0#E-14	( $2^{-14}$ )
DURATION'FIRST	-131072.0000	( $-2^{17}$ )
DURATION'LAST	131071.9999	( $2^{17} - \text{'DELTA}$ )

---

#### F.9.5 Implementation Limits

---

Limit	Description
255	Maximum identifier length (number of characters)
255	Maximum number of characters in a source line
$2^{10}$	Maximum number of library units and subunits in a compilation closure <sup>1</sup>
$2^{12}$	Maximum number of library units and subunits in an execution closure <sup>2</sup>
$-1$	Maximum number of enumeration literals in an enumeration type definition
$2^{16} - 1$	Maximum number of lines in a source file
$2^{31} - 1$	Maximum number of bits in any object
$2^{16} - 1$	Maximum number of exceptions

---

<sup>1</sup>The compilation closure of a given unit is the total set of units that the given unit depends on, directly and indirectly.

<sup>2</sup>The execution closure of a given unit is the compilation closure plus all associated secondary units.

---

---

**LINK**

Creates an executable image file for the specified units.

---

**Format**    **LINK**   *unit-name* [*file-spec*,...]  
               **LINK/NOMAIN**   *unit-name*,...] *file-spec*,...]

**Command Qualifiers**

/AFTER = time  
 /BATCH\_LOG = file-spec  
 /BRIEF  
 /COMMAND[ = file-spec]  
 /[NO]DEBUG[ = file-spec]  
 /ELABORATION = file-spec  
 /FULL  
 /[NO]IMAGE[ = file-spec]  
 /[NO]KEEP  
 /[NO]LOG  
 /[NO]MAIN  
 /[NO]MAP[ = file-spec]  
 /NAME = job-name  
 /[NO]NOTIFY  
 /OUTPUT = file-spec  
 /[NO]PRINTER[ = queue-name]  
 /QUEUE = queue-name  
 /SUBMIT  
 /WAIT

**Defaults**

/AFTER = TODAY  
 See text.  
 See text.  
 See text.  
 /NODEBUG  
 See text.  
 See text.  
 /IMAGE  
 /KEEP  
 /NOLOG  
 /MAIN  
 /NOMAP  
 See text.  
 /NOTIFY  
 /OUTPUT = SYS\$OUTPUT  
 /NOPRINTER  
 /QUEUE = SYS\$BATCH  
 /WAIT  
 /WAIT

**Parameter Qualifiers**

/LIBRARY  
 /MAPPING  
 /TARGET

**Defaults**

See text.  
 See text.  
 See text.

# LINK

---

## Prompts

\_Unit:  
\_File:

---

## Command Parameters

### *unit-name*

By default (or if you specify the /MAIN qualifier):

- You can specify only one unit, the source code of which must be written in XD Ada.
- The parameter *unit-name* specifies the XD Ada main program, which must be a procedure or function with no parameters. If the main program is a function, it must return a value of a discrete type; the function value is used as the VMS image exit value.

If you specify the /NOMAIN qualifier:

- You can specify one or more foreign units that are to be included in the executable image. The unit names may include percent signs (%) and asterisks (\*) as wildcard characters. (See the <REFERENCE> (VMS\_DCL\_CONCEPTS) for detailed information on wildcard characters.)
- The image transfer address comes from one of the foreign files specified.

### *file-spec*

Specifies a list of object files, object libraries, mapping definition files, and target definition files, that are to be used in linking the program. The default directory is the current default directory. The default file type is .XOB, unless the /LIBRARY, /MAPPING, or /TARGET qualifier is used. No wildcard characters are allowed in a file specification.

If the file is an object library or shareable image library, you must use the /LIBRARY qualifier. The default file type is .XLB.

If the file is a mapping definition file, you must use the /MAPPING qualifier. The default file type is .MPD.

If the file is a target definition file you must use the /TARGET qualifier. The default file type is .TGD.

If you specify the /NOMAIN qualifier, the image transfer address comes from one of the files (not units) specified.

---

## Description

The LINK command performs the following steps:

1. Runs the prebuild phase to generate an elaboration list.
2. Checks if a pragma LINK\_OPTION is specified for the main program, and if specified, verifies that the designated link option name is available in the current program library. If available, the copied link option files in the library corresponding to the link option are used, unless overridden by the /TARGET or /MAPPING qualifiers.

Note that, unlike the CHECK command, the pragma LINK\_OPTION association for units other than the main program unit is not checked.

If no target link option is given for the main program unit or the designated target link option is not found in the library, and the logical symbol XDADA\$TARGET\_DEF is not defined, and a /TARGET qualifier is not specified on the LINK command line, an error is issued. If no mapping link option is given for the main program unit or the designated mapping link option is not found in the library, and the logical symbol XDADA\$MAPPING\_DEF is not defined, and a /MAPPING qualifier is not specified on the XDACS LINK command line, the default mapping in the target definition file is used.

3. If LINK/NOMAIN is not specified, checks that only one unit is specified and that it is an XD Ada main program.
4. Forms the closure of the main program (LINK/MAIN) or of the specified units (LINK/NOMAIN) and verifies that all units in the closure are present, current and complete. If XDACS detects an error, the operation is terminated at the end of the prebuild phase.
5. Creates a DCL command file for the builder. The command file is deleted after the LINK operation is completed or terminated, unless LINK/COMMAND is specified. If LINK/COMMAND is specified, the command file is retained for future use, and the build phase is not carried out.



## LINK

6. Unless the /COMMAND qualifier is specified, performs the build phase as follows:
  - a. By default (LINK/WAIT), the command file generated in step 4 is executed in a subprocess. You must wait for the build operation to terminate before issuing another command. Note that when you specify the /WAIT qualifier (the default), process logical names are propagated to the subprocess generated to execute the command file.
  - b. If you specify the /SUBMIT qualifier, the builder command file is submitted as a batch job.
7. If the /DEBUG qualifier is included in the command line the debug symbol table information is placed in a file with a default file type of .XDS.
8. Creates a loadable output file with a default file type of .RLD.

XDACS output originating before the builder is invoked is reported to your terminal by default, or to a file specified with the /OUTPUT qualifier. Diagnostics are reported to your terminal, by default, or to a log file if the LINK command is executed in batch mode (XDACS LINK/SUBMIT).

See <REFERENCE>(target), <REFERENCE>(map), and <REFERENCE>(build) for more information on the XD Ada target-specific builder commands.

---

## Command Qualifiers

### **/AFTER = time**

Requests that the batch job be held until after a specific time, when the LINK command is executed in batch mode (LINK/SUBMIT). If the specified time has already passed, the job is queued for immediate processing.

You can specify either an absolute time or a combination of absolute and delta time. See the <REFERENCE>(VMS\_DCL\_CONCEPTS) (or type HELP Specify Date-Time at the DCL prompt) for complete information on specifying time values.

### **/BATCH\_LOG = file-spec**

Provides a file specification for the batch log file when the LINK command is executed in batch mode (LINK/SUBMIT).

If you do not give a directory specification with the *file-spec* option, the batch log file is created by default in the current default directory. If you do not give a file specification, the default file name is the job name specified with the */NAME=job-name* qualifier. If no job name has been specified, the program library manager creates a file name comprising up to the first 39 characters of the first unit name specified. If you specified LINK/NOMAIN and no job name and there is a wildcard character in the first unit specified, the program library manager uses the default file name XDACS\_LINK. The default file type is .LOG.

### ***/BRIEF***

Directs the builder to produce a brief image map file. The */BRIEF* qualifier is valid only if you also specify the */MAP* qualifier with the LINK command. The */BRIEF* qualifier is incompatible with the */FULL* qualifier.

A brief image map file contains only the following sections:

- Object module information
- Segment mapping information
- Link run statistics

See also the description of the */FULL* qualifier.

### ***/COMMAND[ = file-spec]***

Controls whether the builder is invoked as a result of the LINK command, and determines whether the command file generated to invoke the builder is saved. If you specify the */COMMAND* qualifier, XDACS does not invoke the builder, and the generated command file is saved for you to invoke or submit as a batch job.

The *file-spec* option allows you to enter a file specification for the generated command file. The default directory for the command file is the current default directory. By default, XDACS provides a file name comprising up to the first 39 characters of the first unit name specified. If you specified LINK/NOMAIN and you used a wildcard character in the first name unit specified, the program library manager uses the default file name XDACS\_LINK. The default file type is .COM. No wildcard characters are allowed in the file specification.

By default, if the */COMMAND* qualifier is not specified, XDACS deletes the generated command file when the LINK command completes normally or is terminated.

## LINK

**/DEBUG[ = file-spec]**

**/NODEBUG (D)**

Controls whether a debugger symbol table is created along with the loadable image file.

By default, no debugger symbol table is created.

**/ELABORATION = file-spec**

Provides a file specification for the object file generated by the LINK command. The file is retained by XDACS only when the /COMMAND qualifier is used: that is, when the result of the LINK operation is to produce a builder command file for future use, rather than to invoke the builder immediately.

The generated object file contains the code that directs the elaboration of library packages in the closure of the units specified. Unless you also specify the /NOMAIN qualifier, the object file also contains the image transfer address.

The default directory for the generated object file is the current default directory. The default file type is .XOB. No wildcard characters are allowed in the file specification.

By default, if you do not specify the /ELABORATION qualifier, XDACS provides a file name comprising up to the first 39 characters of the first unit name specified.

By default, if you do not specify the /COMMAND qualifier, XDACS deletes the generated object file when the LINK command completes normally or is terminated.

**/FULL**

Directs the builder to produce a full image map file, which is the most complete image map. The /FULL qualifier is valid only if you also specify the /MAP qualifier with the LINK command. Also, the /FULL qualifier is incompatible with the /BRIEF qualifier.

A full image map file contains the following sections:

- Object module information
- Segment mapping information
- Symbol address information
- Exception numbers
- Link run statistics

**//IMAGE[ = file-spec] (D)**

**/NOIMAGE**

Controls whether the LINK command creates a loadable image file and optionally provides a file specification for the file. The default file type is .RLD. No wildcard characters are allowed in the file specification.

By default, an executable image file is created with a file name comprising up to the first 39 characters of the first unit name specified.

**/KEEP (D)**

**/NOKEEP**

Controls whether the batch log file generated is deleted after it is printed when the LINK command is executed in batch mode (LINK/SUBMIT).

By default, the log file is not deleted.

**/LOG**

**/NOLOG (D)**

Controls whether a list of all the units included in the executable image is displayed. The display shows the units according to the order of elaboration for the program.

By default, a list of all the units included in the executable image is not displayed.

**/MAIN (D)**

**/NOMAIN**

Controls where the image transfer address is to be found.

The /MAIN qualifier indicates that the XD Ada unit specified determines the image transfer address, and hence is to be a main program.

The /NOMAIN qualifier indicates that the image transfer address comes from one of the files specified, and not from one of the XD Ada units specified.

By default (/MAIN), only one XD Ada unit can be specified, and that unit must be an XD Ada main program.

**/MAP[ = file-spec]**

**/NOMAP (D)**

Controls whether the builder creates an image map file and optionally provides a file specification for the file. The default directory for the image map file is the current directory. The default file name comprises up to the first 39 characters of the first unit name specified.

## LINK

The default file type is .MAP. No wildcard characters are allowed in the file specification.

If neither the /BRIEF nor the /FULL qualifier is specified with the /MAP qualifier, /BRIEF is assumed.

By default, no image map file is created.

### **/NAME = job-name**

Specifies a string to be used as the job name and as the file name for the batch log file when the LINK command is executed in batch mode (LINK/SUBMIT). The job name can have from 1 to 39 characters.

By default, if you do not specify the /NAME qualifier, XDACS creates a job name comprising up to the first 39 characters of the first unit name specified. If you specify LINK/NOMAIN but do not specify the /NAME qualifier, and you use a wildcard character in the first unit name specified, the program library manager uses the default file name XDACS\_LINK. In these cases, the job name is also the file name of the batch log file.

### **/NOTIFY (D)**

#### **/NONOTIFY**

Controls whether a message is broadcast when the LINK command is executed in batch mode (LINK/SUBMIT). The message is broadcast to any terminal at which you are logged in, notifying you that your job has been completed or terminated.

By default, a message is broadcast.

### **/OUTPUT = file-spec**

Requests that any output generated before the builder is invoked be written to the file specified rather than to SYS\$OUTPUT. Any diagnostic messages are written to both SYS\$OUTPUT and the file.

The default directory is the current default directory. If you specify a file type but omit the file name, the default file name is XDACS. The default file type is .LIS. No wildcard characters are allowed in the file specification.

By default, the LINK command output is written to SYS\$OUTPUT.

***/PRINTER[ = queue-name]***

***/NOPRINTER (D)***

Controls whether the log file is queued for printing when the LINK command is executed in batch mode (LINK/SUBMIT) and the batch job is completed.

The /PRINTER qualifier allows you to specify a particular print queue. The default print queue for the log file is SYS\$PRINT.

By default, the log file is not queued for printing. If you specify /NOPRINTER, /KEEP is assumed.

***/QUEUE = queue-name***

Specifies the batch job queue in which the job is entered when the LINK command is executed in batch mode (LINK/SUBMIT).

By default, if the /QUEUE qualifier is not specified, the job is placed in the default system batch job queue, SYS\$BATCH.

***/SUBMIT***

Directs XDACS to submit the command file generated for the builder to a batch queue. You can continue to issue commands in your current process without waiting for the batch job to complete. The builder output is written to a batch log file.

By default, the generated command file is executed in a subprocess (LINK/WAIT).

***/WAIT***

Directs XDACS to execute the command file generated for the builder in a subprocess. Execution of your current process is suspended until the subprocess completes. The builder output is written directly to your terminal. Note that process logical names are propagated to the subprocess generated to execute the command file.

By default, XDACS executes the command file generated for the builder in a subprocess: you must wait for the subprocess to terminate before you can issue another command.

---

## Parameter Qualifiers

***/LIBRARY***

Indicates that the associated input file is an object module library to be searched for modules to resolve any undefined symbols in the input files. The default file type is .XLB.

## LINK

By default, if you do not specify the `/LIBRARY` qualifier, the file is assumed to be an object file with a default file type of `.XOB`.

### **`/MAPPING`**

Indicates that the associated input file is a mapping definition file. Mapping definition files control the location of the program on the target system. The default file type is `.MPD`.

By default, if you do not specify the `/MAPPING` qualifier, the file is assumed to be an object file with a default file type of `.XOB`.

### **`/TARGET`**

Indicates that the associated input file is a target definition file. Target definition files describe the target system's memory. The default file type is `.TGD`.

By default, if you do not specify the `/TARGET` qualifier, the file is assumed to be an object file with a default file type of `.XOB`.

---

## Examples

1. `XDACS> LINK CONTROL_LOOP`

`%ACS-I-CL_LINKING`, Invoking the XD Ada Builder

The `LINK` command forms the closure of the unit `CONTROL_LOOP`, which is an XD Ada main program, creates a builder command file and package elaboration file, then invokes the command file in a spawned subprocess.

2. `XDACS> LINK/SUBMIT CONTROL_LOOP LOOP_FUNCTIONS/LIBRARY`

`%ACS-I-CL_SUBMITTED`, Job `CONTROL_LOOP` (queue `ALL_BATCH`, entry 134) started on `FAST_BATCH`

The `LINK` command instructs the builder to link the closure of the XD Ada main program `CONTROL_LOOP` against the library `LOOP_FUNCTIONS.XLB`. The `/SUBMIT` qualifier causes `XDACS` to submit the builder command file as a batch job.

3. ADA/PS> LINK /NOMAIN FLUID\_VOLUME, COUNTER MONITOR.XOB

%AUS-I-01\_LINKING, Invoking the XD Ada Builder

The LINK command builds all the XD Ada units FLUID\_VOLUME and COUNTER with the foreign object file MONITOR.XOB. The /NOMAIN qualifier tells the builder that the image transfer address is in the foreign file.



## XDADA

---

## XDADA

Invokes the XD Ada compiler to compile one or more source files.

---

### Format **XDADA** *file-spec*[,...]

#### Command Qualifiers

/LIBRARY = directory-spec

#### Defaults

/LIBRARY = XDADA\$LIB

#### Positional Qualifiers

/[NO]ANALYSIS\_DATA[ = file-spec]

/[NO]CHECK

/[NO]COPY\_SOURCE

/[NO]DEBUG[ = (option[,...])]

/[NO]DIAGNOSTICS[ = file-spec]

/[NO]ERROR\_LIMIT[ = n]

/[NO]LIST[ = file-spec]

/[NO]LOAD[ = option]

/[NO]MACHINE\_CODE

/[NO]NOTE\_SOURCE

/[NO]OPTIMIZE[ = (option[,...])]

/[NO]PREDEFINED\_UNIT

/[NO]SHOW[ = option]

/[NO]SYNTAX\_ONLY

/[NO]WARNINGS[ = (option[,...])]

#### Defaults

/NOANALYSIS\_DATA

See text.

/COPY\_SOURCE

/DEBUG = ALL

/NODIAGNOSTICS

/ERROR\_LIMIT = 30

/NOLIST

/LOAD = REPLACE

/NOMACHINE\_CODE

/NOTE\_SOURCE

See text.

/NOPREDEFINED\_UNIT

/SHOW = PORTABILITY

/NOSYNTAX\_ONLY

See text.

---

### Prompt

\_File:

---

### Command Parameters

#### *file-spec*

Specifies one or more XD Ada source files to be compiled. If you do not specify a file type, the compiler uses the default file type of .ADA. No wildcard characters are allowed in the file specifications.

If you specify several source files as arguments to the XDADA command, you must separate adjacent file specifications with a comma (.). If you specify more than one input file, you must separate adjacent file specifications with a comma (.). You cannot use a plus sign (+) to separate file specifications.

---

## Description

The XDADA command is one of three commands used to compile compilation units. The other two are the XDACS COMPILE and RECOMPILE commands. All three commands invoke the XD Ada cross-compiler for the <REFERENCE>(proc).

The XDADA command can be used at any time to compile one or more source files (.ADA); it must be used to compile units into a library for the first time or to compile again a set of units where the order of compilation has changed.

XD Ada source files are compiled in the order in which they appear on the command line. If a source file contains more than one XD Ada compilation unit, the units are compiled in the order in which they appear in the source file. The Ada rules governing the order in which compilation units are compiled are summarized in Version 2.0 of <REFERENCE>(dap).

The XDADA command compiles units in the context of the current program library. Whenever a compilation unit is successfully compiled, the current program library is updated as follows:

- An object file (.XOB), which contains the object module, is usually created in the library.
- A compilation unit file (.ACU) is always created in the library.
- Unless suppressed by the /NOCOPY\_SOURCE qualifier on the XDADA command, the file specification of the XD Ada source file is noted in the library.
- The library index file is revised.
- If the unit was previously compiled into the program library, the obsolete versions of the associated library files are deleted.

See <REFERENCE>(prg\_lib\_mgr) and Version 2.0 of <REFERENCE>(dap) for more information on program libraries, sublibraries, and compilation.

---

## Command Qualifiers

### ***/LIBRARY = directory-spec***

Specifies the program library that is to be the current program library for the duration of the compilation. The directory specified must be an already existing XD Ada program library. No wildcard characters are allowed in the directory specification.

By default, the current program library is the program library last specified in a SET LIBRARY command. The logical name XDADA\$LIB is assigned to the program library specified in a SET LIBRARY command.

---

## Positional Qualifiers

### ***/ANALYSIS\_DATA[ = file-spec]***

#### ***/NOANALYSIS\_DATA (D)***

Controls whether a data analysis file containing source code cross-reference and static analysis information is created. The data analysis file is supported only for use with DIGITAL layered products, such as the VAX Source Code Analyzer.

One data analysis file is created for each source file compiled. The default directory for data analysis files is the current default directory. The default file name is the name of the source file being compiled. The default file type is .ANA. No wildcard characters are allowed in the file specification.

By default, no data analysis file is created.

### ***/CHECK***

#### ***/NOCHECK***

Controls whether all run-time checks are suppressed. The /NOCHECK qualifier is equivalent to having all possible SUPPRESS pragmas in the source code.

Explicit use of the /CHECK qualifier overrides any occurrences of the pragmas SUPPRESS and SUPPRESS\_ALL in the source code, without the need to edit the source code.

By default, run-time checks are suppressed only in cases where a pragma SUPPRESS or SUPPRESS\_ALL appears in the source.

See the <REFERENCE>(xlrn) for more information on the pragmas SUPPRESS and SUPPRESS\_ALL.

**/COPY\_SOURCE (D)****/NOCOPY\_SOURCE**

Controls whether a copied source file (.ADC) is created in the current program library when a compilation unit is compiled without error. The RECOMPILE command (and thus the COMPILE command) requires that a copied source file exist in the current program library for any unit that is to be recompiled.

By default, a copied source file is created in the current program library when a unit is compiled without error.

**/DEBUG[=(option[...])] (D)****/NODEBUG**

Controls which compiler debugging options are provided. You can debug XD Ada programs with the XD Ada Debugger (see <REFERENCE>(debug\_ch)). You can request the following options:

ALL	Provides both SYMBOLS and TRACEBACK.
NONE	Provides neither SYMBOLS nor TRACEBACK.
[NO]SYMBOLS	Controls whether debugger symbol records are included in the object file.
[NO]TRACEBACK	Controls whether traceback information (a subset of the debugger symbol information) is included in the object file.

By default, both debugger symbol records and traceback information are included in the object file (/DEBUG=ALL, or equivalently: /DEBUG).

**/DIAGNOSTICS[=file-spec]****/NODIAGNOSTICS (D)**

Controls whether a diagnostics file containing compiler messages and diagnostic information is created. The diagnostics file is supported only for use with DIGITAL layered products, such as the VAX Language-Sensitive Editor.

One diagnostics file is created for each source file compiled. The default directory for diagnostics files is the current default directory. The default file name is the name of the source file being compiled. The default file type is .DIA. No wildcard characters are allowed in the file specification.

By default, no diagnostics file is created.

**ERROR\_LIMIT[=n]**  
**NOERROR\_LIMIT**

Controls whether execution of the XDADA command for a given compilation unit is terminated upon the occurrence of the nth E-level error within that unit.

Error counts are not accumulated across a sequence of compilation units. If the ERROR\_LIMIT=n option is specified, each compilation unit may have up to n-1 errors without terminating the compilation. When the error limit is reached within a compilation unit, compilation of that unit is terminated, but compilation of subsequent units continues.

The ERROR\_LIMIT=0 option is equivalent to ERROR\_LIMIT=1.

By default, execution of the XDADA command is terminated for a given compilation unit upon the occurrence of the 30th E-level error within that unit (equivalent to ERROR\_LIMIT=30).

**/LIST[=file-spec]**  
**/NOLIST (D)**

Controls whether a listing file is created. One listing file is created for each source file compiled. The default directory for listing files is the current default directory. The default file name is the name of the source file being compiled. The default file type is .LIS. No wildcard characters are allowed in the file specification.

By default, the XDADA command does not create a listing file.

**/LOAD[=option]**  
**/NOLOAD**  
**LOAD=REPLACE (D)**

Controls whether the current program library is updated with the successfully processed units contained in the specified source files. Depending on other qualifiers specified (or not specified) with the ADA command, processing can involve full compilation, syntax checking only, and so on. The /NOLOAD qualifier causes the units in the specified source files to be processed, but prevents the current program library from being updated.

You can specify the following option:

**[NO]REPLACE**

Controls whether a unit added to the current program library replaces an existing unit with the same name. If you specify the **NOREPLACE** option, the unit is added to the current program library only if no existing unit has the same name, except if the new unit is the corresponding body of an existing specification or vice versa.

By default, the current program library is updated with the successfully processed units, and a unit added to the current program library replaces an existing unit with the same name.

**/MACHINE\_CODE**

**/NOMACHINE\_CODE (D)**

Controls whether generated machine code (approximating assembly language notation) is included in the listing file.

By default, generated machine code is not included in the listing file.

**/NOTE\_SOURCE (D)**

**/NONOTE\_SOURCE**

Controls whether the file specification of the source file is noted in the program library when a unit is compiled without error. The **COMPILE** command uses this information to locate revised source files.

By default, the file specification of the source file is noted in the program library when a unit is compiled without error.

**/OPTIMIZE[ = (option[,...])]**

**/NOOPTIMIZE**

Controls the level of optimization that is applied in producing the compiled code. You can specify one of the following primary options:

TIME	Provides full optimization with time as the primary optimization criterion. Overrides any occurrences of the pragma <b>OPTIMIZE(SPACE)</b> in the source code.
SPACE	Provides full optimization with space as the primary optimization criterion. Overrides any occurrences of the pragma <b>OPTIMIZE(TIME)</b> in the source code.

## XDADA

DEVELOPMENT	Recommended when active development of a program is in progress. Provides some optimization, but development considerations and ease of debugging take preference over optimization. This option overrides pragmas that establish a dependence on a subprogram (the pragma <code>INLINE</code> ), and thus reduces the need for recompilations when such bodies are modified.
NONE	Provides no optimization. Suppresses expansions in line of subprograms, including those specified by the pragma <code>INLINE</code> .

The `/NOOPTIMIZE` qualifier is equivalent to `/OPTIMIZE=NONE`.

By default, the XDADA command applies full optimization with space as the primary optimization criterion (like `/OPTIMIZE=SPACE`, but observing uses of the pragma `OPTIMIZE`).

The `/OPTIMIZE` qualifier also has a set of secondary options that you can use separately or together with the primary options to override the default behavior for expansion in line.

The `INLINE` secondary option can have the following values (see the `<REFERENCE>` (rts) for more information about expansion in line).

<code>INLINE:NONE</code>	Disables subprogram expansion in line. This option overrides any occurrences of the pragma <code>INLINE</code> in the source code, without having to edit the source file. It also disables implicit expansion in line of subprograms. ( <i>Implicit expansion in line</i> means that the compiler assumes a pragma <code>INLINE</code> for certain subprograms as an optimization.) A call to a subprogram in another unit is not expanded in line, regardless of the <code>/OPTIMIZE</code> options in effect when that unit was compiled.
<code>INLINE:NORMAL</code>	Provides normal subprogram expansion in line. Subprograms to which an explicit pragma <code>INLINE</code> applies are expanded in line under certain conditions. In addition, some subprograms are implicitly expanded in line. The compiler assumes a pragma <code>INLINE</code> for calls to some small local subprograms (subprograms that are declared in the same unit as the unit in which the call occurs).

**INLINE:SUBPROGRAMS** Provides maximal subprogram expansion in line.

In addition to the normal subprogram expansion in line that occurs when **INLINE:NORMAL** is specified, this option results in implicit expansion in line of some small subprograms declared in other units. The compiler assumes a pragma **INLINE** for any subprogram if it improves execution speed and reduces code size. This option may establish a dependence on the body of another unit, as would be the case if a pragma **INLINE** were specified explicitly in the source code.

**INLINE:MAXIMAL** Provides maximal subprogram expansion in line. Maximal subprogram expansion in line occurs as for **INLINE:SUBPROGRAMS**.

By default, the **/OPTIMIZE** qualifier primary options have the following secondary-option values:

<b>/OPTIMIZE=TIME</b>	<b>=(INLINE:NORMAL)</b>
<b>/OPTIMIZE=SPACE</b>	<b>=(INLINE:NORMAL)</b>
<b>/OPTIMIZE=DEVELOPMENT</b>	<b>=(INLINE:NONE)</b>
<b>/OPTIMIZE=NONE</b>	<b>=(INLINE:NONE)</b>

See Chapter 3 of Version 2.0 of <REFERENCE>(dap) for a further discussion of the **/OPTIMIZE** qualifier and its options.

#### ***/PREDEFINED\_UNIT***

#### ***/NOPREDEFINED\_UNIT (D)***

Controls the compilation of package **\$RUN\_TIME\_SYSTEM**, package **\$TASKING\_SYSTEM**, and package **MACHINE\_CODE**. You must specify this qualifier in order to be able to compile these packages. The qualifier is not required for the compilation of any other source files. See the <REFERENCE>(rts) for more information.

By default, **/PREDEFINED\_UNIT** is omitted.



## XDADA

**/SHOW[=option] (D)**

**/NOSHOW**

Controls the listing file options included when a listing file is provided. You can specify one of the following options:

ALL	Provides all listing file options.
[NO]PORTABILITY	Controls whether a program portability summary is included in the listing file. By default, the XDADA command provides a portability summary (/SHOW=PORTABILITY). See <REFERENCE>(port_summ) for details of what can be included in a portability summary. See Chapter 5 of Version 2.0 of <REFERENCE>(dap) for more information on program portability.
NONE	Provides none of the listing file options (same as NOSHOW).

By default, the XDADA command provides a portability summary (/SHOW=PORTABILITY).

**/SYNTAX\_ONLY**

**/NOSYNTAX\_ONLY (D)**

Controls whether the source file is to be checked only for correct syntax. If you specify the /SYNTAX\_ONLY qualifier, other compiler checks are not performed (for example, semantic analysis, type checking, and so on), and the program library is not updated.

By default, the compiler performs all checks.

**/WARNINGS[=(message-option[,...])]**

**/NOWARNINGS**

Controls which categories of informational (I-level) and warning (W-level) messages are displayed and where those messages are displayed. You can specify any combination of the following message options:

WARNINGS: (destination[,...])  
NOWARNINGS

WEAK\_WARNINGS: (destination[,...])  
NOWEAK\_WARNINGS

SUPPLEMENTAL: (destination[,...])  
NOSUPPLEMENTAL

COMPILATION\_NOTES: (*destination*[,...])  
 NOCOMPILATION\_NOTES

STATUS: (*destination*[,...])  
 NOSTATUS

The possible values of *destination* are ALL, NONE, or any combination of TERMINAL (terminal device), LISTING (listing file), DIAGNOSTICS (diagnostics file). The message categories are summarized as follows:

WARNINGS	W-level: Indicates a definite problem in a legal program, for example, an unknown pragma.
WEAK_WARNINGS	I-level: Indicates a potential problem in a legal program; for example, a possible CONSTRAINT_ERROR at run time. These are the only kind of I-level messages that are counted in the summary statistics at the end of a compilation.
SUPPLEMENTAL	I-level: Additional information associated with preceding E-level or W-level diagnostics.
COMPILATION_NOTES	I-level: Information about how the compiler translated a program, such as record layout, parameter-passing mechanisms, or decisions made for the pragmas INLINE, INTERFACE, or the import-subprogram pragmas.
STATUS	I-level: End of compilation statistics and other messages.

The defaults are as follows:

```
/WARNINGS=(WARN:ALL,WEAK:ALL,SUPP:ALL,COMP:NONE,STAT:LIST)
```

If you specify only some of the message categories with the /WARNINGS qualifier, the default values for other categories are used.

---

## Examples

1. \$ XDADA MODEL\_INTERFACE\_,MODEL\_INTERFACE,CONTROL\_LOOP

The XDADA command compiles the compilation units contained in the three files MODEL\_INTERFACE\_.ADA, MODEL\_INTERFACE.ADA, and CONTROL\_LOOP.ADA, in the order given.

## XDADA

2. \$ XDADA/LIST/SHOW=ALL SCREEN\_IO\_,SCREEN\_IO

The XDADA command compiles the compilation units contained in the two files SCREEN\_IO\_.ADA and SCREEN\_IO.ADA, in the order given. The /LIST qualifier creates the listing files SCREEN\_IO\_.LIS and SCREEN\_IO.LIS in the current default directory. The /SHOW=ALL qualifier causes all listing file options to be provided in the listing files.

## APPENDIX C

## TEST PARAMETERS

Certain tests in the ACVC make use of implementation-dependent values, such as the maximum length of an input line and invalid file names. A test that makes use of such values is identified by the extension .TST in its file name. Actual values to be substituted are represented by names that begin with a dollar sign. A value must be substituted for each of these names before the test is run. The values used for this validation are given below:

<u>Name and Meaning</u>	<u>Value</u>
\$ACC_SIZE An integer literal whose value is the number of bits sufficient to hold any value of an access type.	32
\$BIG_ID1 Identifier the size of the maximum input line length with varying last character.	(1..254=>'A', 255=>1)
\$BIG_ID2 Identifier the size of the maximum input line length with varying last character.	(1..254=>'A', 255=>2)
\$BIG_ID3 Identifier the size of the maximum input line length with varying middle character.	(1..127=>'A', 128=>3, 129..255=>'A')
\$BIG_ID4 Identifier the size of the maximum input line length with varying middle character.	(1..127=>'A', 128=>4, 129..255=>'A')
\$BIG_INT_LIT An integer literal of value 298 with enough leading zeroes so that it is the size of the maximum line length	(1..252=>0, 253..255=>298)
\$BIG_REAL_LIT A universal real literal of value 690.0 with enough leading zeroes to be the size of the maximum line length.	(1..249=>0, 250..255=>69.0E1)
\$BIG_STRING1 A string literal which when catenated with BIG_STRING2 yields the image of BIG_ID1.	(1..127=>'A')

---

\$BIG_STRING2	(1..127=>'A', 128=>1)
A string literal which when catenated to the end of BIG_STRING1 yields the image of BIG_ID1.	
\$BLANKS	(1..235=>' ')
A sequence of blanks twenty characters less than the size of the maximum line length.	
\$COUNT_LAST	2147483647
A universal integer literal whose value is TEXT_IO.COUNT'LAST.	
\$DEFAULT_MEM_SIZE	16777216
An integer literal whose value is SYSTEM.MEMORY_SIZE.	
\$DEFAULT_STOR_UNIT	8
An integer literal whose value is SYSTEM.STORAGE_UNIT.	
\$DEFAULT_SYS_NAME	MC68000
The value of the constant SYSTEM.SYSTEM_NAME.	
\$DELTA_DOC	2#1.0#E-31
A real literal whose value is SYSTEM.FINE_DELTA.	
\$FIELD_LAST	255
A universal integer literal whose value is TEXT_IO.FIELD'LAST.	
\$FIXED_NAME	NO_SUCH_TYPE
The name of a predefined fixed-point type other than DURATION.	
\$FLOAT_NAME	LONG_LONG_FLOAT
The name of a predefined floating-point type other than FLOAT, SHORT_FLOAT, or LONG_FLOAT.	
\$GREATER_THAN_DURATION	131072.0
A universal real literal that lies between DURATION'BASE'LAST and DURATION'LAST or any value in the range of DURATION.	
\$GREATER_THAN_DURATION_BASE_LAST	131073.0
A universal real literal that is greater than DURATION'BASE'LAST.	

## TEST PARAMETERS

---

<b>\$HIGH_PRIORITY</b>	15
An integer literal whose value is the upper bound of the range for the subtype SYSTEM.PRIORITY.	
<b>\$ILLEGAL_EXTERNAL_FILE_NAME1</b>	THERE ARE NO ILLEGAL FILENAMES
An external file name which contains invalid characters.	
<b>\$ILLEGAL_EXTERNAL_FILE_NAME2</b>	N/A
An external file name which is too long.	
<b>\$INTEGER_FIRST</b>	-2147483648
A universal integer literal whose value is INTEGER'FIRST.	
<b>\$INTEGER_LAST</b>	2147483647
A universal integer literal whose value is INTEGER'LAST.	
<b>\$INTEGER_LAST_PLUS_1</b>	2147483648
A universal integer literal whose value is INTEGER'LAST+1.	
<b>\$LESS_THAN_DURATION</b>	-131072.0
A universal real literal that lies between DURATION'BASE'FIRST and DURATION'FIRST or any value in the range of DURATION.	
<b>\$LESS_THAN_DURATION_BASE_FIRST</b>	-131073.0
A universal real literal that is less than DURATION'BASE'FIRST.	
<b>\$LOW_PRIORITY</b>	0
An integer literal whose value is the lower bound of the range for the subtype SYSTEM.PRIORITY.	
<b>\$MANTISSA_DOC</b>	31
An integer literal whose value is SYSTEM.MAX_MANTISSA.	
<b>\$MAX_DIGITS</b>	18
Maximum digits supported for floating-point types.	
<b>\$MAX_IN_LEN</b>	255
Maximum input line length permitted by the implementation.	

## TEST PARAMETERS

\$MAX_INT	2147483647
A universal integer literal whose value is SYSTEM.MAX_INT.	
\$MAX_INT_PLUS_1	2147483648
A universal integer literal whose value is SYSTEM.MAX_INT+1.	
\$MAX_LEN_INT_BASED_LITERAL	(1..2=>'2:', 3..252=>'0', 253..255=>'11:')
A universal integer based literal whose value is 2#11# with enough leading zeroes in the mantissa to be MAX_IN_LEN long.	
\$MAX_LEN_REAL_BASED_LITERAL	(1..3=>'16:', 4..251=>'0', 252..255=>'F.E:')
A universal real based literal whose value is 16:F.E: with enough leading zeroes in the mantissa to be MAX_IN_LEN long.	
\$MAX_STRING_LITERAL	(1=>'"', 2..254=>'A', 255=>'")
A string literal of size MAX_IN_LEN, including the quote characters.	
\$MIN_INT	-2147483648
A universal integer literal whose value is SYSTEM.MIN_INT.	
\$MIN_TASK_SIZE	32
An integer literal whose value is the number of bits required to hold a task object which has no entries, no declarations, and "NULL;" as the only statement in its body.	
\$NAME	SHORT_SHORT_INTEGER
A name of a predefined numeric type other than FLOAT, INTEGER, SHORT_FLOAT, SHORT_INTEGER, LONG_FLOAT, or LONG_INTEGER.	
\$NAME_LIST	MC68000
A list of enumeration literals in the type SYSTEM.NAME, separated by commas.	
\$NEG_BASED_INT	16#FFFF_FFFF#
A based integer literal whose highest order nonzero bit falls in the sign bit position of the representation for SYSTEM.MAX_INT.	

---

<b>\$NEW_MEM_SIZE</b>	123456
An integer literal whose value is a permitted argument for pragma memory_size, other than \$DEFAULT_MEM_SIZE. If there is no other value, then use \$DEFAULT_MEM_SIZE.	
<b>\$NEW_STOR_UNIT</b>	8
An integer literal whose value is a permitted argument for pragma storage_unit, other than \$DEFAULT_STOR_UNIT. If there is no other permitted value, then use value of SYSTEM.STORAGE_UNIT.	
<b>\$NEW_SYS_NAME</b>	MC68000
A value of the type SYSTEM.NAME, other than \$DEFAULT_SYS_NAME. If there is only one value of that type, then use that value.	
<b>\$TASK_SIZE</b>	32
An integer literal whose value is the number of bits required to hold a task object which has a single entry with one inout parameter.	
<b>\$TICK</b>	2#1.0#E-13
A real literal whose value is SYSTEM.TICK.	



## APPENDIX D

## WITHDRAWN TESTS

Some tests are withdrawn from the ACVC because they do not conform to the Ada Standard. The following 44 tests had been withdrawn at the time of validation testing for the reasons indicated. A reference of the form AI-ddddd is to an Ada Commentary.

- E28005C This test expects that the string "-- TOP OF PAGE. --63" of line 204 will appear at the top of the listing page due to a pragma PAGE in line 203; but line 203 contains text that follows the pragma, and it is this that must appear at the top of the page.
- A39005G This test unreasonably expects a component clause to pack an array component into a minimum size (line 30).
- B97102E This test contains an unintended illegality: a select statement contains a null statement at the place of a selective wait alternative (line 31).
- C97116A This test contains race conditions, and it assumes that guards are evaluated indivisibly. A conforming implementation may use interleaved execution in such a way that the evaluation of the guards at lines 50 & 54 and the execution of task CHANGING\_OF\_THE\_GUARD results in a call to REPORT.FAILED at one of lines 52 or 56.
- BC3009B This test wrongly expects that circular instantiations will be detected in several compilation units even though none of the units is illegal with respect to the units it depends on; by AI-00256, the illegality need not be detected until execution is attempted (line 95).
- CD2A62D This test wrongly requires that an array object's size be no greater than 10 although its subtype's size was specified to be 40 (line 137).
- CD2A63A..D, CD2A66A..D, CD2A73A..D, CD2A76A..D [16 tests]  
These tests wrongly attempt to check the size of objects of a derived type (for which a 'SIZE length clause is given) by passing them to a derived subprogram (which implicitly converts them to the parent type (Ada standard 3.4.14)). Additionally, they use the 'SIZE length clause and attribute, whose interpretation is considered problematic by the WG9 ARG.
- CD2A81G, CD2A83G, CD2A84N & M, & CD5011O [5 tests]  
These tests assume that dependent tasks will terminate while the main program executes a loop that simply tests for task termination; this is not the case, and the main program may loop indefinitely (lines 74, 85, 86 & 96, 86 & 96, and 58, resp.).

---

CD2B15C & CD7205C

These tests expect that a 'STORAGE\_SIZE length clause provides precise control over the number of designated objects in a collection; the Ada standard 13.2:15 allows that such control must not be expected.

CD2D11B This test gives a SMALL representation clause for a derived fixed-point type (at line 30) that defines a set of model numbers that are not necessarily represented in the parent type; by Commentary AI-00099, all model numbers of a derived fixed-point type must be representable values of the parent type.

CD5007B This test wrongly expects an implicitly declared subprogram to be at the the address that is specified for an unrelated subprogram (line 303).

ED7004B, ED7005C & D, ED7006C & D [5 tests]

These tests check various aspects of the use of the three SYSTEM pragmas; the AVO withdraws these tests as being inappropriate for validation.

CD7105A This test requires that successive calls to CALENDAR.CLOCK change by at least SYSTEM.TICK; however, by Commentary AI-00201, it is only the expected frequency of change that must be at least SYSTEM.TICK--particular instances of change may be less (line 29).

CD7203B, & CD7204B

These tests use the 'SIZE length clause and attribute, whose interpretation is considered problematic by the WG9 ARG.

CD7205D This test checks an invalid test objective: it treats the specification of storage to be reserved for a task's activation as though it were like the specification of storage for a collection.

CE2107I This test requires that objects of two similar scalar types be distinguished when read from a file--DATA\_ERROR is expected to be raised by an attempt to read one object as of the other type. However, it is not clear exactly how the Ada standard 14.2.4:4 is to be interpreted; thus, this test objective is not considered valid. (line 90)

CE3111C This test requires certain behavior, when two files are associated with the same external file, that is not required by the Ada standard.

CE3301A This test contains several calls to END\_OF\_LINE & END\_OF\_PAGE that have no parameter: these calls were intended to specify a file, not to refer to STANDARD\_INPUT (lines 103, 107, 118, 132, & 136).

CE3411B This test requires that a text file's column number be set to COUNT'LAST in order to check that LAYOUT\_ERROR is raised by a subsequent PUT operation. But the former operation will generally raise an exception due to a lack of available disk space, and the test would thus encumber validation testing.

## N C C V S R A D D E N D U M

This Addendum to the ACVC 1.10 VSR clarifies some items which are contained within the standard pre-forma Validation Summary Report as supplied by the Ada Maintenance Office (AMO).

In line with AJPO regulations the contents of the VSR have not been altered in order to keep consistency between the different AVF's.

The points raised in this addendum are being addressed by the AMO in future issues of the VSR.

- 1 The last paragraph of Chapter 1 contains the following statement 'Any test that was determined to contain an illegal language construct or an erroneous language construct is withdrawn from the ACVC...'

This is incorrect since illegal constructs are legitimately contained within Class B tests.

- 2 Both the terms 'inapplicable' and 'not applicable' are used within the VSR. These terms are identical.

- 3 Chapter 1 of the VSR does not indicate how 'inapplicable' tests are to be analysed. The analysis is undertaken as follows:

'Each inapplicable test is checked to ensure that this behaviour is consistent with the given reasons for its inapplicability'.

# REPORT DOCUMENTATION PAGE

Form Approved  
OPM No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE	3. REPORT TYPE AND DATES COVERED Final 4 Feb. 1990 to 4 Feb. 1991	
4. TITLE AND SUBTITLE Ada Compiler Validation Summary Report: SD-Scicon plc, XD Ada MC68000 V1.0-09, VAX Cluster (Host) to MC68000 (Target), 90Q204N1.10252			5. FUNDING NUMBERS	
6. AUTHOR(S) National Computing Centre Limited Manchester, UNITED KINGDOM			8. PERFORMING ORGANIZATION REPORT NUMBER AVF-VSR-90502/66	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Computing Centre Limited Oxford Road Manchester M1 7ED UNITED KINGDOM			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Ada Joint Program Office United States Department of Defense Washington, D.C. 20301-3081			11. SUPPLEMENTARY NOTES	
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  SD-Scicon plc, XD Ada MC68000 V1.0-09, Manchester, England, VAX Cluster (Comprising of a VAX 8600 and 7 MicroVAX II's) under VMS 5.1 (Host) to MC68000 processor running on an MVME117-3FP MPU VME module using a MC68881 floating point peripheral (bare machine), ACVC 1.10.				
14. SUBJECT TERMS Ada programming language, Ada Compiler Validation Summary Report, Ada Compiler Validation Capability, Validation Testing, Ada Validation Office, Ada Validation Facility, ANSI/MIL-STD-1815A, Ada Joint Program Office			15. NUMBER OF PAGES	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED			18. PRICE CODE	
16. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT

AVF Control Number: AVF-VSR-90502/66

Ada COMPILER  
VALIDATION SUMMARY REPORT:  
Certificate Number: #900204N1.10252  
SD-Scicon plc  
XD Ada MC63000 V1.0-09  
VAX Cluster Host and MC68000 target

Completion of On-Site Testing:  
February 4 1990

Prepared By:  
Testing Services  
The National Computing Centre Limited  
Oxford Road  
Manchester M1 7ED  
England

Prepared For:  
Ada Joint Program Office  
United States Department of Defense  
Washington DC 20301-3081

Ada Compiler Validation Summary Report:

Compiler Name: XD Ada MC68000 V1.0-09

Certificate Number: #900204N1.10252

Host: VAX Cluster (Comprising of a VAX 8600 and 7 MicroVAX II's) under VMS 5.1

Target: MC68000 processor running on an MVME117-3FP MPU VME module using a MC68881 floating point peripheral (bare machine).

Testing Completed February 4 1990 Using ACVC 1.10

This report has been reviewed and is approved.

*J. Pink*

Jane Pink  
Testing Services Manager  
The National Computing Centre Limited  
Oxford Road  
Manchester M1 7ED  
England

*Dr. John F. Kramer*

for  
Ada Validation Organization  
Dr. John F. Kramer  
Institute for Defense Analyses  
Alexandria VA 22311

*John P. Solomond*

Ada Joint Program Office  
Dr. John Solomond  
Director AJPO  
Department of Defense  
Washington DC 20301

---

TABLE OF CONTENTS

CHAPTER 1	
INTRODUCTION .....	1
1.1 PURPOSE OF THIS VALIDATION SUMMARY REPORT .....	1
1.2 USE OF THIS VALIDATION SUMMARY REPORT .....	2
1.3 REFERENCES .....	2
1.4 DEFINITION OF TERMS .....	3
1.5 ACVC TEST CLASSES .....	4
CHAPTER 2	
CONFIGURATION INFORMATION .....	1
2.1 CONFIGURATION TESTED .....	1
2.2 IMPLEMENTATION CHARACTERISTICS .....	1
CHAPTER 3	
TEST INFORMATION .....	1
3.1 TEST RESULTS .....	1
3.2 SUMMARY OF TEST RESULTS BY CLASS .....	1
3.3 SUMMARY OF TEST RESULTS BY CHAPTER .....	1
3.4 WITHDRAWN TESTS .....	2
3.5 INAPPLICABLE TESTS .....	2
3.6 TEST, PROCESSING, AND EVALUATION MODIFICATIONS ..	5
3.7 ADDITIONAL TESTING INFORMATION .....	5
APPENDIX A	
DECLARATION OF CONFORMANCE .....	1
APPENDIX B	
APPENDIX F OF THE Ada STANDARD .....	1
APPENDIX C	
TEST PARAMETERS .....	1
APPENDIX D	
WITHDRAWN TESTS .....	1

## CHAPTER 1

## INTRODUCTION

This Validation Summary Report (VSR) describes the extent to which a specific Ada compiler conforms to the Ada Standard, ANSI/MIL-STD-1815A. This report explains all technical terms used within it and thoroughly reports the results of testing this compiler using the Ada Compiler Validation Capability (ACVC). An Ada compiler must be implemented according to the Ada Standard, and any implementation-dependent features must conform to the requirements of the Ada Standard. The Ada Standard must be implemented in its entirety, and nothing can be implemented that is not in the Standard.

Even though all validated Ada compilers conform to the Ada Standard, it must be understood that some differences do exist between implementations. The Ada Standard permits some implementation dependencies -- for example, the maximum length of identifiers or the maximum values of integer types. Other differences between compilers result from the characteristics of particular operating systems, hardware, or implementation strategies. All the dependencies observed during the process of testing this compiler are given in this report.

The information in this report is derived from the test results produced during validation testing. The validation process includes submitting a suite of standardized tests, the ACVC, as inputs to an Ada compiler and evaluating the results. The purpose of validating is to ensure conformity of the compiler to the Ada Standard by testing that the compiler properly implements legal language constructs and that it identifies and rejects illegal language constructs. The testing also identifies behavior that is implementation dependent, but is permitted by the Ada Standard. Six classes of tests are used. These tests are designed to perform checks at compile time, at link time, and during execution.

### 1.1 PURPOSE OF THIS VALIDATION SUMMARY REPORT

This VSR documents the results of the validation testing performed on an Ada compiler. Testing was carried out for the following purposes:

- o To attempt to identify any language constructs supported by the compiler that do not conform to the Ada Standard
- o To attempt to identify any language constructs not supported by the compiler but required by the Ada Standard
- o To determine that the implementation-dependent behavior is allowed by the Ada Standard

Testing of this compiler was conducted by The National Computer Centre Limited according to procedures established by the Ada Joint Program Office and administered by the Ada Validation



Organization (AVO). On-site testing was completed on February 4 1990 at SD-SCICON plc, Pembroke House, Pembroke Broadway, Camberley, Surrey, GU15 3XD, UK.

### 1.2 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the AVO may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject compiler has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from:

Ada Information Clearinghouse  
Ada Joint Program Office  
OUSDRE  
The Pentagon, Rm 3D-139 (Fern Street)  
Washington DC 20301-3081

or from:

Testing Services  
The National Computing Centre Limited  
Oxford Road  
Manchester M1 7ED  
England

Questions regarding this report or the validation test results should be directed to the AVF listed above or to:

Ada Validation Organization  
Institute for Defense Analyses  
1801 North Beauregard Street  
Alexandria VA 22311

### 1.3 REFERENCES

1. Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
2. Ada Compiler Validation Procedures and Guidelines, Ada Joint Program Office, 1 January 1987.

3. Ada Compiler Validation Capability Implementers' Guide, SofTech, Inc., December 1986.
4. Ada Compiler Validation Capability User's Guide, December 1986.

## 1.4 DEFINITION OF TERMS

ACVC	The Ada Compiler Validation Capability. The set of Ada programs that tests the conformity of an Ada compiler to the Ada programming language.
Ada Commentary	An Ada Commentary contains all information relevant to the point addressed by a comment on the Ada Standard. These comments are given a unique identification number having the form AI-ddddd.
Ada Standard	ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
Applicant	The agency requesting validation.
AVF	The Ada Validation Facility. The AVF is responsible for conducting compiler validations according to procedures contained in the <u>Ada Compiler Validation Procedures and Guidelines</u> .
AVO	The Ada Validation Organization. The AVO has oversight authority over all AVF practices for the purpose of maintaining a uniform process for validation of Ada compilers. The AVO provides administrative and technical support for Ada validations to ensure consistent practices.
Compiler	A processor for the Ada language. In the context of this report, a compiler is any language processor, including cross-compilers, translators, and interpreters.
Failed test	An ACVC test for which the compiler generates a result that demonstrates nonconformity to the Ada Standard.
Host	The computer on which the compiler resides.
Inapplicable test	An ACVC test that uses features of the language that a compiler is not required to support or may legitimately support in a way other than the one expected by the test.
Passed test	An ACVC test for which a compiler generates the expected result.

---

Target	The computer which executes the code generated by the compiler.
Test	A program that checks a compiler's conformity regarding a particular feature or a combination of features to the Ada Standard. In the context of this report, the term is used to designate a single test, which may comprise one or more files.
Withdrawn test	An ACVC test found to be incorrect and not used to check conformity to the Ada Standard. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains illegal or erroneous use of the language.

### 1.5 ACVC TEST CLASSES

Conformity to the Ada Standard is measured using the ACVC. The ACVC contains both legal and illegal Ada programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable, and special program units are used to report their results during execution. Class B tests are expected to produce compilation errors. Class L tests are expected to produce errors because of the way in which a program library is used at link time.

Class A tests ensure the successful compilation and execution of legal Ada programs with certain language constructs which cannot be verified at run time. There are no explicit program components in a Class A test to check semantics. For example, a Class A test checks that reserved words of another language (other than those already reserved in the Ada language) are not treated as reserved words by an Ada compiler. A Class A test is passed if no errors are detected at compile time and the program executes to produce a PASSED message.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that every syntactic or semantic error in the test is detected. A Class B test is passed if every illegal construct that it contains is detected by the compiler.

Class C tests check the run time system to ensure that legal Ada programs can be correctly compiled and executed. Each Class C test is self-checking and produces a PASSED, FAILED, or NOT APPLICABLE message indicating the result when it is executed.

Class D tests check the compilation and execution capacities of a compiler. Since there are no capacity requirements placed on a compiler by the Ada Standard for some parameters -- for example, the number of identifiers permitted in a compilation or the number of units in a library -- a compiler may refuse to compile a Class D test and still be a conforming compiler. Therefore, if a Class D test fails to compile because the capacity of the compiler is exceeded, the test is classified as inapplicable. If a Class D test compiles successfully, it is self-checking and produces a PASSED or FAILED message during execution.

Class E tests are expected to execute successfully and check implementation-dependent options and resolutions of ambiguities in the Ada Standard. Each Class E test is self-checking and produces a NOT APPLICABLE, PASSED, or FAILED message when it is compiled and executed. However, the Ada Standard permits an implementation to reject programs containing some features addressed by Class E tests during compilation. Therefore, a Class E test is passed by a compiler if it is compiled successfully and executes to produce a PASSED message, or if it is rejected by the compiler for an allowable reason.

Class L tests check that incomplete or illegal Ada programs involving multiple, separately compiled units are detected and not allowed to execute. Class L tests are compiled separately and execution is attempted. A Class L test passes if it is rejected at link time -- that is, an attempt to execute the main program must generate an error message before any declarations in the main program or any units referenced by the main program are elaborated. In some cases, an implementation may legitimately detect errors during compilation of the test.

Two library units, the package REPORT and the procedure CHECK\_FILE, support the self-checking features of the executable tests. The package REPORT provides the mechanism by which executable tests report PASSED, FAILED, or NOT APPLICABLE results. It also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The procedure CHECK\_FILE is used to check the contents of text files written by some of the Class C tests for Chapter 14 of the Ada Standard. The operation of REPORT and CHECK\_FILE is checked by a set of executable tests. These tests produce messages that are examined to verify that the units are operating correctly. If these units are not operating correctly, then the validation is not attempted.

The text of each test in the ACVC follows conventions that are intended to ensure that the tests are reasonably portable without modification. For example, the tests make use of only the basic set of 55 characters, contain lines with a maximum length of 72 characters, use small numeric values, and place features that may not be supported by all implementations in separate tests. However, some tests contain values that require the test to be customized according to implementation-specific values -- for example, an illegal file name. A list of the values used for this validation is provided in Appendix C.

A compiler must correctly process each of the tests in the suite and demonstrate conformity to the Ada Standard by either meeting the pass criteria given for the test or by showing that the test is inapplicable to the implementation. The applicability of a test to an implementation is considered each time the implementation is validated. A test that is inapplicable for one validation is not necessarily inapplicable for a subsequent validation. Any test that was determined to contain an illegal language construct or an erroneous language construct is withdrawn from the ACVC and, therefore, is not used in testing a compiler. The tests withdrawn at the time of this validation are given in Appendix D.

## CHAPTER 2

### CONFIGURATION INFORMATION

#### 2.1 CONFIGURATION TESTED

The candidate compilation system for this validation was tested under the following configuration:

Compiler:	XD Ada MC68000 V1.0-09		
ACVC Version:	1.10		
Certificate Number:	#900204N1.10252		
Host Computer:			
Machine:	VAX Cluster (comprising of a VAX 8600 and 7 MicroVAX II's)		
Operating System:	VMS 5.1		
Memory Size:	VAX 8600	-	20Mbytes
	MicroVAX II's	-	1 x 16 Mbytes
			6 x 9 Mbytes
Target Computer:			
Machine:	MC68000 processor running on an MVME117-3FP MPU VME module using an MC68881 floating point peripheral.		
Operating System	Bare machine.		
Memory Size:	512Kb		
Communications Network:	RS232 link		

#### 2.2 IMPLEMENTATION CHARACTERISTICS

One of the purposes of validating compilers is to determine the behavior of a compiler in those areas of the Ada Standard that permit implementations to differ. Class D and E tests specifically check for such implementation differences. However, tests in other classes also characterize an implementation. The tests demonstrate the following characteristics:

a. Capacities.

- (1) The compiler correctly processes a compilation containing 723 variables in the same declarative part. (See test D29002K.)
- (2) The compiler correctly processes tests containing loop statements nested to 65 levels. (See tests D55A03A..H (8 tests).)
- (3) The compiler correctly processes tests containing block statements nested to 65 levels. (See test D56001B.)
- (4) The compiler correctly processes tests containing recursive procedures separately compiled as subunits nested to 17 levels. (See tests D64005E..G (3 tests).)

b. Predefined types.

- (1) This implementation supports the additional predefined types SHORT\_INTEGER, SHORT\_SHORT\_INTEGER, LONG\_FLOAT, and LONG\_LONG\_FLOAT, in the package STANDARD. (See tests B86001T..Z (7 tests).)

c. Expression evaluation.

The order in which expressions are evaluated and the time at which constraints are checked are not defined by the language. While the ACVC tests do not specifically attempt to determine the order of evaluation of expressions, test results indicate the following:

- (1) None of the default initialization expressions for record components are evaluated before any value is checked for membership in a component's subtype. (See test C32117A.)
- (2) Assignments for subtypes are performed with the same precision as the base type. (See test C35712B).
- (3) This implementation uses no extra bits for extra precision and uses all extra bits for extra range. (See test C35903A.)
- (4) NUMERIC\_ERROR is raised when an integer literal operand in a comparison or membership test is outside the range of the base type. (See test C45232A.)
- (5) NUMERIC\_ERROR is raised when a literal operand in a fixed-point comparison or membership test is outside the range of the base type. (See test C45252A.)
- (6) Underflow is gradual. (See tests C45524A..Z (26 tests).)

d. Rounding.

The method by which values are rounded in type conversions is not defined by the language. While the ACVC tests do not specifically attempt to determine the method of rounding, the test results indicate the following:

- (1) The method used for rounding to integer is round to even. (See tests C46012A..Z (26 tests).)
- (2) The method used for rounding to longest integer is round to even. See tests C46012A..Z (26 tests).)
- (3) The method used for rounding to integer in static universal real expressions is round away from zero. (See test C4A014A.)

e. Array types.

An implementation is allowed to raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` for an array having a `'LENGTH` that exceeds `STANDARD.INTEGER'LAST` and/or `SYSTEM.MAX_INT`. For this implementation:

- (1) Declaration of an array type or subtype declaration with more than `SYSTEM.MAX_INT` components raises `NUMERIC_ERROR`. (See test C36003A.)
- (2) `NUMERIC_ERROR` is raised when an array type with `INTEGER'LAST + 2` components is declared. (See test C36202A.)
- (3) `NUMERIC_ERROR` is raised when an array type with `SYSTEM.MAX_INT + 2` components is declared. (See test C36202B.)
- (4) A packed `BOOLEAN` array having a `'LENGTH` exceeding `INTEGER'LAST` raises `NUMERIC_ERROR` when the array type is declared. (See test C52103X.)
- (5) A packed two-dimensional `BOOLEAN` array with more than `INTEGER'LAST` components `NUMERIC_ERROR` when the array type is declared. (See test C52104Y.)
- (6) In assigning one-dimensional array types, the expression is evaluated in its entirety before `CONSTRAINT_ERROR` is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)
- (7) In assigning two-dimensional array types, the expression is not evaluated in its entirety before `CONSTRAINT_ERROR` is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- f. A null array with one dimension of length greater than INTEGER'LAST may raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` either when declared or assigned. Alternatively, an implementation may accept the declaration. However, lengths must match in array slice assignments. This implementation raises no exception. (See test E52103Y.)
- g. Discriminated types.
  - (1) In assigning record types with discriminants, the expression is evaluated in its entirety before `CONSTRAINT_ERROR` is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)
- h. Aggregates.
  - (1) In the evaluation of a multi-dimensional aggregate, the test results indicate that all choices are evaluated before checking against the index type. (See tests C43207A and C43207B.)
  - (2) In the evaluation of an aggregate containing subaggregates, all choices are evaluated before being checked for identical bounds. (See test E43212B.)
  - (3) `CONSTRAINT_ERROR` is raised after all choices are evaluated when a bound in a non-null range of a non-null aggregate does not belong to an index subtype. (See test E43211B.)
- i. Pragmas.
  - (1) The pragma `INLINE` is supported for functions or procedures. (See tests LA3004A..B (2 tests), EA3004C..D (2 tests), and CA3004E..F (2 tests).)
- j. Generics.
  - (1) Generic specifications and bodies can be compiled in separate compilations. (See tests CA1012A, CA2009C, CA2009F, BC3204C, and BC3205D.)
  - (2) Generic subprogram declarations and bodies can be compiled in separate compilations. (See tests CA1012A and CA2009F.)
  - (3) Generic library subprogram specifications and bodies can be compiled in separate compilations. (See test CA1012A.)
  - (4) Generic non-library package bodies as subunits can be compiled in separate compilations. (See test CA2009C.)



- (5) Generic non-library subprogram bodies can be compiled in separate compilations from their stubs. (See test CA2009F.)
  - (6) Generic unit bodies and their subunits can be compiled in separate compilations. (See test CA3011A.)
  - (7) Generic package declarations and bodies can be compiled in separate compilations. (See tests CA2009C, BC3204C, and BC3205D.)
  - (8) Generic library package specifications and bodies can be compiled in separate compilations. (See tests BC3204C and BC3205D.)
- k. Input and output.
- (1) The package SEQUENTIAL\_IO can be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101C, EE2201D, and EE2201E.)
  - (2) The package DIRECT\_IO can be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101H, EE2401D, and EE2401G.)
  - (3) The director, AJPO, has determined (AI-00332) that every call to OPEN and CREATE must raise USE\_ERROR or NAME\_ERROR if file input/output is not supported. This implementation exhibits this behavior for SEQUENTIAL\_IO, DIRECT\_IO, and TEXT\_IO.

## CHAPTER 3

## TEST INFORMATION

**3.1 TEST RESULTS**

Version 1.10 of the ACVC comprises 3717 tests. When this compiler was tested, 44 tests had been withdrawn because of test errors. The AVF determined that 504 tests were inapplicable to this implementation. All inapplicable tests were processed during validation testing except for 159 executable tests that use floating-point precision exceeding that supported by the implementation. Modifications to the code, processing, or grading for 16 tests were required to successfully demonstrate the test objective. (See section 3.6.)

The AVF concludes that the testing results demonstrate acceptable conformity to the Ada Standard.

**3.2 SUMMARY OF TEST RESULTS BY CLASS**

RESULT	TEST CLASS						TOTAL
	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>	<u>L</u>	
Passed	129	1133	1828	17	16	46	3169
Inapplicable	0	5	487	0	12	0	504
Withdrawn	1	2	35	0	6	0	44
TOTAL	130	1140	2350	17	34	46	3717

**3.3 SUMMARY OF TEST RESULTS BY CHAPTER**

RESULT	CHAPTER														TOTAL
	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>	<u>7</u>	<u>8</u>	<u>9</u>	<u>10</u>	<u>11</u>	<u>12</u>	<u>13</u>	<u>14</u>		
Passed	201	592	567	245	172	99	162	331	137	36	252	295	78	3169	
Inapp	11	57	111	3	0	0	4	1	0	0	0	74	243	504	
Withdrawn	1	1	0	0	0	0	0	2	0	0	1	35	4	44	
TOTAL	213	650	680	248	172	99	166	334	137	36	253	404	325	3717	

### 3.4 WITHDRAWN TESTS

The following 44 tests were withdrawn from ACVC Version 1.10 at the time of this validation:

E28005C	A39005G	B97102E
C97116A	BC3009B	CD2A62D
CD2A63A..D (4 tests)	CD2A66A..D (4 tests)	CD2A73A..D (4 tests)
CD2A76A..D (4 tests)	CD2A81G	CD2A83G
CD2A84M..N (2 tests)	CD2B15C	CD2D11B
CD5007B	CD5011O	ED7004B
ED7005C..D (2 tests)	ED7006C..D (2 tests)	CD7105A
CD7203B	CD7204B	CD7205C
CD7205D	CE2107I	CE3111C
CE3301A	CE3411B	

See Appendix D for the reason that each of these tests was withdrawn.

### 3.5 INAPPLICABLE TESTS

Some tests do not apply to all compilers because they make use of features that a compiler is not required by the Ada Standard to support. Others may depend on the result of another test that is either inapplicable or withdrawn. The applicability of a test to an implementation is considered each time a validation is attempted. A test that is inapplicable for one validation attempt is not necessarily inapplicable for a subsequent attempt. For this validation attempt, 504 tests were inapplicable for the reasons indicated:

- a. The following 159 tests are not applicable because they have floating-point type declarations requiring more digits than SYSTEM.MAX\_DIGITS:

C24113O..Y (11 tests)	C35705O..Y (11 tests)	C35706O..Y (11 tests)
C35707O..Y (11 tests)	C35708O..Y (11 tests)	C35802O..Z (12 tests)
C45241O..Y (11 tests)	C45321O..Y (11 tests)	C45421O..Y (11 tests)
C45521O..Z (12 tests)	C45524O..Z (12 tests)	C45621O..Z (12 tests)
C45641O..Y (11 tests)	C46012O..Z (12 tests)	

- b. C35702A and B86001T are not applicable because this implementation supports no predefined type SHORT\_FLOAT.

- c. The following 16 tests are not applicable because this implementation does not support a predefined type LONG\_INTEGER:

C45231C	C45304C	C45502C	C45503C	C45504C
C45504F	C45611C	C45613C	C45614C	C45631C
C45632C	B52004D	C55B07A	B55B09C	
B86001W	CD7101F			

- 
- d. C45531M..P (4 tests) and C45532M..P (4 tests) are all inapplicable because this implementation has a 'MAX\_MANTISSA of 31 and these tests require the compiler to support a greater value.
- e. C86001F is not applicable because, for this implementation, the package TEXT\_IO is dependent upon package SYSTEM. This test recompiles package SYSTEM, making package TEXT\_IO, and hence package REPORT, obsolete.
- f. B86001Y is not applicable because this implementation supports no predefined fixed-point type other than DURATION.
- g. C96005B is not applicable because there are no values of type DURATION'BASE that are outside the range of DURATION.
- h. CD1009C, CD2A41A..B (2 tests), CD2A41E and CD2A42A..J (10 tests) are not applicable because 'SIZE representation clauses for floating-point types are not supported.
- i. CD1C04C is inapplicable because this implementation does not support model numbers of a derived type that are not representable values of the parent type.
- j. CD2A52C..D (2 tests), CD2A52G..H (2 tests), CD2A54C..D (2 tests) and CD2A54H are not applicable because for this implementation the legality of a 'SIZE clause for a derived fixed point type can depend on the representation chosen for the parent type.
- k. CD2A53C, and CD2A54G are not applicable because within these tests the SMALL specified for a derived fixed point is finer than the SMALL for the parent type. As a result some model numbers of the derived type are not representable values of the parent type which this implementation does not allow.
- l. The following 23 tests are not applicable because this implementation does not support packing by means of a length clause for an array type:
- CD2A61A..L (12 tests)      CD2A62A..C (3 tests)      CD2A64A..D (4 tests)  
CD2A65A..D (4 tests)
- m. The following 16 tests are not applicable because this implementation does not support packing by means of a length clause for a record type:
- CD2A71A..D (4 tests)      CD2A72A..D (4 tests)      CD2A74A..D (4 tests)  
CD2A75A..D (4 tests)
- n. CD2A84B..I (8 tests) and CD2A84K..L (2 tests) are not applicable because this implementation only accepts length clause for access types, if the default size (32 bits) is specified. These tests specify sizes other than 32 bits.

- o. The following 241 tests are inapplicable because sequential, text, and direct access files are not supported:

CE2102A..C (3 tests)	CE2102G..H (2 tests)	CE2102K
CE2102N..Y (12 tests)	CE2103C..D (2 tests)	CE2104A..D (4 tests)
CE2105A..B (2 tests)	CE2106A..B (2 tests)	CE2107A..H (8 tests)
CE2107L	CE2108A..H (8 tests)	CE2109A..C (3 tests)
CE2110A..D (4 tests)	CE2111A..I (9 tests)	CE2115A..B (2 tests)
CE2201A..C (3 tests)	EE2201D..E (2 tests)	CE2201F..N (9 tests)
CE2204A..D (4 tests)	CE2205A	CE2208B
CE2401A..C (3 tests)	EE2401D	CE2401E..F (2 tests)
EE2401G	CE2401H..L (5 tests)	CE2404A..B (2 tests)
CE2405B	CE2406A	CE2407A..B (2 tests)
CE2408A..B (2 tests)	CE2409A..B (2 tests)	CE2410A..B (2 tests)
CE2411A	CE3102A..B (2 tests)	EE3102C
CE3102F..H (3 tests)	CE3102J..K (2 tests)	CE3103A
CE3104A..C (3 tests)	CE3107B	CE3108A..B (2 tests)
CE3109A	CE3110A	CE3111A..B (2 tests)
CE3111D..E (2 tests)	CE3112A..D (4 tests)	CE3114A..B (2 tests)
CE3115A	EE3203A	CE3208A
EE3301B	CE3302A	CE3305A
CE3402A	EE3402B	CE3402C..D (2 tests)
CE3403A..C (3 tests)	CE3403E..F (2 tests)	CE3404B..D (3 tests)
CE3405A	EE3405B	CE3405C..D (2 tests)
CE3406A..D (4 tests)	CE3407A..C (3 tests)	CE3408A..C (3 tests)
CE3409A	CE3409C..E (3 tests)	EE3409F
CE3410A	CE3410C..E (3 tests)	EE3410F
CE3411A	CE3411C	CE3412A
CE3413A	CE3413C	CE3602A..D (4 tests)
CE3603A	CE3604A..B (2 tests)	CE3605A..E (5 tests)
CE3606A..B (2 tests)	CE3704A..F (6 tests)	CE3704M..O (3 tests)
CE3706D	CE3706F..G (2 tests)	CE3804A..P (16 tests)
CE3805A..B (2 tests)	CE3806A..B (2 tests)	CE3806D..E (2 tests)
CE3806G..H (2 tests)	CE3905A..C (3 tests)	CE3905L
CE3906A..C (3 tests)	CE3906E..F (2 tests)	

- p. CE3901A is not applicable because this implementation raises NAME\_ERROR if a filename parameter to TEXT\_IO.CREATE is non-null. This test assumes that USE\_ERROR will be raised.
- q. EE3412C is not applicable for this implementation because their implementation of the body of the package report does not use TEXT\_IO.

### 3.6 TEST, PROCESSING, AND EVALUATION MODIFICATIONS

It is expected that some tests will require modifications of code, processing, or evaluation in order to compensate for legitimate implementation behaviour. Modifications are made by the AVF in cases where legitimate implementation behaviour prevents the successful completion of an (otherwise) applicable test. Examples of such modifications include: adding a length clause to alter the default size of a collection; splitting a Class B test into subtests so that all errors are detected; and confirming that messages produced by an executable test demonstrate conforming behaviour that was not anticipated by the test (such as raising one exception instead of another).

Modifications were required for 16 tests.

C34006D is classified as passed if the test fails with messages "INCORRECT TYPE'SIZE" or "INCORRECT OBJECT'SIZE". This test incorrectly assumes that the space allocated for objects must be less than or equal to the minimum needed by the (sub) type. This is not true for this implementation.

C45524A..N (14 tests) were modified because these tests expect that the result of continued division of a real number will be zero; the Ada Standard, however, only requires that the result be within the type's SAFE\_SMALL of zero. Thus, these tests were modified to include a check that the result was in the smallest positive safe interval for the type. The implementation passed the modified tests. Each test was modified by inserting the following code after line 138;

The following test was split because syntax errors at one point resulted in the compiler not detecting other errors in the test:

B97103E

### 3.7 ADDITIONAL TESTING INFORMATION

#### 3.7.1 Prevalidation

Prior to validation, a set of test results for ACVC Version 1.10 produced by the **XD Ada MC68000 V1.0-09** compiler was submitted to the AVF by the applicant for review. Analysis of these results demonstrated that the compiler successfully passed all applicable tests, and the compiler exhibited the expected behaviour on all inapplicable tests.

#### 3.7.2 Test Method

Testing of the **XD Ada MC68000 V1.0-09** compiler using ACVC Version 1.10 was conducted on-site by a validation team from the AVF. The configuration in which the testing was performed is described by the following designations of hardware and software components:

---

Host computer	: VAX Cluster (comprising of a VAX 8600 and 7 MicroVAX II's)
Host operating system	: VMS 5.1
Target computer	: MC68000 processor running on the MVME117-3FP MPU VME module using an MC68881 floating point peripheral.
Compiler	: XD Ada MC68000 V1.0-09
Assembler	: XD Ada MC68000 V1.0-09
Linker	: XD Ada MC68030 V1.0-04
Loader	: XD Ada MC68000 S1.0-10
Downloader	: XD Ada MC68030 V1.0-04
Runtime System	: XD Ada MC68000 V1.0-09

The host and target computers were linked via a RS232 link.

A magnetic tape containing all tests except for withdrawn tests and tests requiring unsupported floating-point precisions was taken on-site by the validation team for processing. Tests that make use of implementation-specific values were customized before being written to the magnetic tape. Tests requiring modifications during the prevalidation testing were not included in their modified form on the magnetic tape.

The contents of the magnetic tape were loaded directly onto the host computer.

After the test files were loaded to disk, the full set of tests was compiled and linked on the VAX Cluster, then all executable images were transferred to the MC68000 target via the RS232 link and run. Results were printed from the host computer.

The compiler was tested using command scripts provided by SD-Scicon plc and reviewed by the validation team. The compiler was tested using all the following option settings. Details of these settings are given at the end of Appendix B.

Tests were compiled, linked, and executed (as appropriate) using 8 computers and two target computers. Test output, compilation listings, and job logs were captured on magnetic media and archived at the AVF. The listings examined on-site by the validation team were also archived.

### 3.7.3 Test Site

Testing was conducted at SD-Scicon plc, Pembroke House, Pembroke Broadway, Camberley, Surrey, GU15 3XD, UK and was completed on February 4 1990.

## DECLARATION OF CONFORMANCE

---

### APPENDIX A

#### DECLARATION OF CONFORMANCE

SD-Scicon plc has submitted the following Declaration of Conformance concerning the XD Ada MC68000 V1.0-09 compiler.



## DECLARATION OF CONFORMANCE

### DECLARATION OF CONFORMANCE

Compiler Implementor: SD-Scicon plc  
Ada Validation Facility: The National Computing Centre Limited  
Oxford Road  
Manchester  
M1 7ED


Ada Compiler Validation Capability (ACVC) Version: 1.10

#### Base Configuration

Base Compiler Name: XD Ada MC68000 V1.0-09  
Host Architecture: VAX Cluster (comprising of a VAX 8600 and 7  
MicroVAX II's)  
Host OS and Version: VMS 5.1  
Target Architecture: MC68000 processor on an MVME117-3FP MPU  
VME module using an MC68881 floating point  
peripheral (bare machine).

#### Implementor's Declaration

I, the undersigned, representing SD-Scicon plc, have implemented no deliberate extensions to the Ada Language Standard ANSI/MIL-STD-1815A in the compiler(s) listed in this declaration. I declare that SD-Scicon plc is the owner of record of the Ada language compiler(s) listed above and, as such, is responsible for maintaining said compiler(s) in conformance to ANSI/MIL-STD-1815A. All certificates and registrations for Ada language compiler(s) listed in this declaration shall be made only in the owner's corporate name.



Date : 25 April 90

Bill Davison  
WORLDWIDE CUSTOMER SERVICES MANAGER

## DECLARATION OF CONFORMANCE

---

### Owner's Declaration

I, the undersigned, representing **SD-Scicon plc**, take full responsibility for implementation and maintenance of the Ada compiler(s) listed above, and agree to the public disclosure of the final Validation Summary Report. I declare that all of the Ada language compilers listed, and their host/target performance, are in compliance with the Ada Language Standard ANSI/MIL-STD-1815A.



Date : 25 April 90

**Bill Davison**  
**WORLDWIDE CUSTOMER SERVICES MANAGER**

## APPENDIX B

## APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in chapter 13 of the Ada Standard, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of the **XD Ada MC68000 V1.0-09** compiler, as described in this Appendix, are provided by **SD-Scicon plc**. Unless specifically noted otherwise, references in this appendix are to compiler documentation and not to this report. Implementation-specific portions of the package STANDARD, which are not a part of Appendix F, are:

package STANDARD is

...

type INTEGER is range -2147483648 .. 2147483647;

type SHORT\_INTEGER is range -32768 .. 32767;

type SHORT\_SHORT\_INTEGER is range -128 .. 127;

type FLOAT is digits 6 range  $-(2^{128} - 2^{104}) ..$

$2^{128} - 2^{104};$

type LONG\_FLOAT is digits 15 range  $-(2^{1024} - 2^{971}) ..$

$2^{1024} - 2^{971};$

type LONG\_LONG\_FLOAT is digits 18 range  $(-2^{16384} - 2^{16320}) ..$

$2^{16384} - 2^{16320}$

type DURATION is delta 1.E-4 range -131072.0000 .. 131071.9999;

...

end STANDARD;

## Implementation-Dependent Characteristics

---

---

### F.3 Specification of Package System

The package SYSTEM for the MC68000 configuration differs from that of the standard MC68020 as follows:

---

#### F.3.1 Changes to Package SYSTEM for the MC68000 Target

```
type NAME is (MC68000);  
SYSTEM_NAME : constant NAME := MC68000;  
STORAGE_UNIT : constant := 8;  
MEMORY_SIZE : constant := 2**24;  
TICK : constant := 2#1.0#E-13;  
type ADDRESS_INT is range 0 .. MEMORY_SIZE-1;  
for ADDRESS_INT'SIZE use 32;
```

---

## **F.6 Interpretation of Expressions Appearing in Address Clauses**

For address clauses on variables, the address expression is interpreted as a Motorola 24-bit address.

In XD Ada for MC68000, values of type `SYSTEM.ADDRESS` are interpreted as integers in the range  $0 \dots 2^{24} - 1$ .

# Implementation-Dependent Characteristics

---

## NOTE

This appendix is not part of the standard definition of the Ada programming language.

This appendix summarizes the following implementation-dependent characteristics of XD Ada:

- Listing the XD Ada pragmas and attributes.
- Giving the specification of the package SYSTEM.
- Presenting the restrictions on representation clauses and unchecked type conversions.
- Giving the conventions for names denoting implementation-dependent components in record representation clauses.
- Giving the interpretation of expressions in address clauses.
- Presenting the implementation-dependent characteristics of the input-output packages.
- Presenting other implementation-dependent characteristics.

---

## F.1 Implementation-Dependent Pragmas

XD Ada provides the following pragmas, which are defined elsewhere in the text. In addition, XD Ada restricts the predefined language pragmas `INLINE` and `INTERFACE`, provides pragma `VOLATILE` in addition to pragma `SHARED`, and provides pragma `SUPPRESS_ALL` in addition to pragma `SUPPRESS`. See Annex B for a descriptive pragma summary.

- `CALL_SEQUENCE_FUNCTION` (see Annex B)
- `CALL_SEQUENCE_PROCEDURE` (see Annex B)
- `EXPORT_EXCEPTION` (see Section 13.9a.3.2)
- `EXPORT_FUNCTION` (see Section 13.9a.1.2)
- `EXPORT_OBJECT` (see Section 13.9a.2.2)
- `EXPORT_PROCEDURE` (see Section 13.9a.1.2)
- `IMPORT_EXCEPTION` (see Section 13.9a.3.1)
- `IMPORT_FUNCTION` (see Section 13.9a.1.1)
- `IMPORT_OBJECT` (see Section 13.9a.2.1)
- `IMPORT_PROCEDURE` (see Section 13.9a.1.1)
- `LEVEL` (see Section 13.5.1)
- `LINK_OPTION` (see Annex B)
- `SUPPRESS_ALL` (see Section 11.7)
- `TITLE` (see Annex B)
- `VOLATILE` (see Section 9.11)

---

## F.2 Implementation-Dependent Attributes

XD Ada provides the following attributes, which are defined elsewhere in the text. See Appendix A for a descriptive attribute summary.

- `BIT` (see Section 13.7.2)
- `MACHINE_SIZE` (see Section 13.7.2)
- `TYPE_CLASS` (see Section 13.7a.2)

---

## F.3 Specification of the Package System

The package SYSTEM for the MC68020 is as follows:

---

### F.3.1 Package System for the MC68020 Target

package SYSTEM is

```
    type NAME is (MC68020);

    SYSTEM_NAME      : constant NAME := MC68020;
    STORAGE_UNIT     : constant := 8;
    MEMORY_SIZE      : constant := 2**31-1;
    MIN_INT           : constant := -(2**31);
    MAX_INT           : constant := 2**31-1;
    MAX_DIGITS        : constant := 18;
    MAX_MANTISSA      : constant := 31;
    FINE_DELTA        : constant := 2.0*(-31);
    TICK              : constant := 162.5E-6;
    subtype PRIORITY is INTEGER range 0 .. 15;

    subtype LEVEL is INTEGER range 0 .. 7;

-- Address type
--
    type ADDRESS is private;

    ADDRESS_ZERO : constant ADDRESS;
    type ADDRESS_INT is range MIN_INT .. MAX_INT;
    function TO_ADDRESS      (X : ADDRESS_INT)           return ADDRESS;
    function TO_ADDRESS      (X : {universal_integer})    return ADDRESS;
    function TO_ADDRESS_INT  (X : ADDRESS)               return ADDRESS_INT;

    function "+" (LEFT : ADDRESS;      RIGHT : ADDRESS_INT) return ADDRESS;
    function "+" (LEFT : ADDRESS_INT;   RIGHT : ADDRESS)    return ADDRESS;
    function "-" (LEFT : ADDRESS;      RIGHT : ADDRESS)    return ADDRESS_INT;
    function "-" (LEFT : ADDRESS;      RIGHT : ADDRESS_INT) return ADDRESS;

-- function "-" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
-- function "/" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function "<" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function "<=" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function ">" (LEFT, RIGHT : ADDRESS) return BOOLEAN;
    function ">=" (LEFT, RIGHT : ADDRESS) return BOOLEAN;

--
-- Note that because ADDRESS is a private type
-- the functions "=" and "/" are already available
```



```

-- Generic functions used to access memory
--
generic
  type TARGET is private;
  function FETCH_FROM_ADDRESS (A : ADDRESS) return TARGET;
generic
  type TARGET is private;
  procedure ASSIGN_TO_ADDRESS (A : ADDRESS; T : TARGET);
  type TYPE_CLASS is (TYPE_CLASS_ENUMERATION,
    TYPE_CLASS_INTEGER,
    TYPE_CLASS_FIXED_POINT,
    TYPE_CLASS_FLOATING_POINT,
    TYPE_CLASS_ARRAY,
    TYPE_CLASS_RECORD,
    TYPE_CLASS_ACCESS,
    TYPE_CLASS_TASK,
    TYPE_CLASS_ADDRESS);

--
-- XD Ada hardware-oriented types and functions
--
type BIT_ARRAY is array (INTEGER range <>) of BOOLEAN;
pragma PACK(BIT_ARRAY);
subtype BIT_ARRAY_8 is BIT_ARRAY (0 .. 7);
subtype BIT_ARRAY_16 is BIT_ARRAY (0 .. 15);
subtype BIT_ARRAY_32 is BIT_ARRAY (0 .. 31);
subtype BIT_ARRAY_64 is BIT_ARRAY (0 .. 63);
type UNSIGNED_BYTE is range 0 .. 255;
for UNSIGNED_BYTE'SIZE use 8;
function "not" (LEFT : UNSIGNED_BYTE) return UNSIGNED_BYTE;
function "and" (LEFT, RIGHT : UNSIGNED_BYTE) return UNSIGNED_BYTE;
function "or" (LEFT, RIGHT : UNSIGNED_BYTE) return UNSIGNED_BYTE;
function "xor" (LEFT, RIGHT : UNSIGNED_BYTE) return UNSIGNED_BYTE;

function TO_UNSIGNED_BYTE (X : BIT_ARRAY_8) return UNSIGNED_BYTE;
function TO_BIT_ARRAY_8 (X : UNSIGNED_BYTE) return BIT_ARRAY_8;

type UNSIGNED_BYTE_ARRAY is array (INTEGER range <>) of UNSIGNED_BYTE;

type UNSIGNED_WORD is range 0 .. 65535;
for UNSIGNED_WORD'SIZE use 16;

function "not" (LEFT : UNSIGNED_WORD) return UNSIGNED_WORD;
function "and" (LEFT, RIGHT : UNSIGNED_WORD) return UNSIGNED_WORD;
function "or" (LEFT, RIGHT : UNSIGNED_WORD) return UNSIGNED_WORD;
function "xor" (LEFT, RIGHT : UNSIGNED_WORD) return UNSIGNED_WORD;

function TO_UNSIGNED_WORD (X : BIT_ARRAY_16) return UNSIGNED_WORD;
function TO_BIT_ARRAY_16 (X : UNSIGNED_WORD) return BIT_ARRAY_16;

type UNSIGNED_WORD_ARRAY is array (INTEGER range <>) of UNSIGNED_WORD;

--
type UNSIGNED_LONGWORD is range MIN_INT .. MAX_INT;
for UNSIGNED_LONGWORD'SIZE use 32;

```

#### F-4 Implementation-Dependent Characteristics

```

function "not" (LEFT      : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;
function "and" (LEFT, RIGHT : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;
function "or"  (LEFT, RIGHT : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;
function "xor" (LEFT, RIGHT : UNSIGNED_LONGWORD) return UNSIGNED_LONGWORD;

function TO_UNSIGNED_LONGWORD (X : BIT_ARRAY_32) return UNSIGNED_LONGWORD;
function TO_BIT_ARRAY_32      (X : UNSIGNED_WORD) return BIT_ARRAY_32;

type UNSIGNED_LONGWORD_ARRAY is array (INTEGER range <>) of UNSIGNED_LONGWORD;

-- Conventional names for static subtypes of type UNSIGNED_LONGWORD
--
subtype UNSIGNED_1  is UNSIGNED_LONGWORD range 0 .. 2** 1-1;
subtype UNSIGNED_2  is UNSIGNED_LONGWORD range 0 .. 2** 2-1;
subtype UNSIGNED_3  is UNSIGNED_LONGWORD range 0 .. 2** 3-1;
subtype UNSIGNED_4  is UNSIGNED_LONGWORD range 0 .. 2** 4-1;
subtype UNSIGNED_5  is UNSIGNED_LONGWORD range 0 .. 2** 5-1;
subtype UNSIGNED_6  is UNSIGNED_LONGWORD range 0 .. 2** 6-1;
subtype UNSIGNED_7  is UNSIGNED_LONGWORD range 0 .. 2** 7-1;
subtype UNSIGNED_8  is UNSIGNED_LONGWORD range 0 .. 2** 8-1;
subtype UNSIGNED_9  is UNSIGNED_LONGWORD range 0 .. 2** 9-1;
subtype UNSIGNED_10 is UNSIGNED_LONGWORD range 0 .. 2**10-1;
subtype UNSIGNED_11 is UNSIGNED_LONGWORD range 0 .. 2**11-1;
subtype UNSIGNED_12 is UNSIGNED_LONGWORD range 0 .. 2**12-1;
subtype UNSIGNED_13 is UNSIGNED_LONGWORD range 0 .. 2**13-1;
subtype UNSIGNED_14 is UNSIGNED_LONGWORD range 0 .. 2**14-1;
subtype UNSIGNED_15 is UNSIGNED_LONGWORD range 0 .. 2**15-1;
subtype UNSIGNED_16 is UNSIGNED_LONGWORD range 0 .. 2**16-1;
subtype UNSIGNED_17 is UNSIGNED_LONGWORD range 0 .. 2**17-1;
subtype UNSIGNED_18 is UNSIGNED_LONGWORD range 0 .. 2**18-1;
subtype UNSIGNED_19 is UNSIGNED_LONGWORD range 0 .. 2**19-1;
subtype UNSIGNED_20 is UNSIGNED_LONGWORD range 0 .. 2**20-1;
subtype UNSIGNED_21 is UNSIGNED_LONGWORD range 0 .. 2**21-1;
subtype UNSIGNED_22 is UNSIGNED_LONGWORD range 0 .. 2**22-1;
subtype UNSIGNED_23 is UNSIGNED_LONGWORD range 0 .. 2**23-1;
subtype UNSIGNED_24 is UNSIGNED_LONGWORD range 0 .. 2**24-1;
subtype UNSIGNED_25 is UNSIGNED_LONGWORD range 0 .. 2**25-1;
subtype UNSIGNED_26 is UNSIGNED_LONGWORD range 0 .. 2**26-1;
subtype UNSIGNED_27 is UNSIGNED_LONGWORD range 0 .. 2**27-1;
subtype UNSIGNED_28 is UNSIGNED_LONGWORD range 0 .. 2**28-1;
subtype UNSIGNED_29 is UNSIGNED_LONGWORD range 0 .. 2**29-1;
subtype UNSIGNED_30 is UNSIGNED_LONGWORD range 0 .. 2**30-1;
subtype UNSIGNED_31 is UNSIGNED_LONGWORD range 0 .. 2**31-1;

private
-- Not shown
end SYSTEM;

```

---

## **F.4 Restrictions on Representation Clauses**

The representation clauses allowed in XD Ada are length, enumeration, record representation, and address clauses.

In XD Ada, a representation clause for a generic formal type or a type that depends on a generic formal type is not allowed. In addition, a representation clause for a composite type that has a component or subcomponent of a generic formal type or a type derived from a generic formal type is not allowed.

Restrictions on length clauses are specified in Section 13.2; restrictions on enumeration representation clauses are specified in Section 13.3; and restrictions on record representation clauses are specified in Section 13.4.

---

## **F.5 Conventions for Implementation-Generated Names Denoting Implementation-Dependent Components in Record Representation Clauses**

XD Ada does not allocate implementation-dependent components in records.

---

## **F.6 Interpretation of Expressions Appearing in Address Clauses**

Expressions appearing in address clauses must be of the type ADDRESS defined in package SYSTEM (see Section 13.7a.1 and Section F.3).

XD Ada allows address clauses for variables (see Section 13.5). For address clauses on variables, the address expression is interpreted as a Motorola full 32-bit address.

XD Ada supports address clauses on task entries to allow interrupts to cause a reschedule directly. For address clauses on task entries, the address expression is interpreted as a Motorola exception vector offset.

In XD Ada for MC68020, values of type SYSTEM.ADDRESS are interpreted as integers in the range 0 ..  $2^{32} - 1$ . As SYSTEM.ADDRESS is a private type, the only operations allowed on objects of this type are those given in package SYSTEM.

---

## F.7 Restrictions on Unchecked Type Conversions

XD Ada supports the generic function UNCHECKED\_CONVERSION with the restrictions given in Section 13.10.2.

---

## F.8 Implementation-Dependent Characteristics of Input-Output Packages

The packages SEQUENTIAL\_IO and DIRECT\_IO are implemented as null packages that conform to the specification given in the *Reference Manual for the Ada Programming Language*. The packages raise the exceptions specified in Chapter 14 of the *Reference Manual for the Ada Programming Language*. The three possible exceptions that are raised by these packages are given here, in the order in which they are raised.

Exception	When Raised
STATUS_ERROR	Raised by an attempt to operate upon or close a file that is not open (no files can be opened).
NAME_ERROR	Raised if a file name is given with a call of CREATE or OPEN.
USE_ERROR	Raised if exception STATUS_ERROR is not raised.

MODE\_ERROR cannot be raised since no file can be opened (therefore it cannot have a current mode).

The predefined package LOW\_LEVEL\_IO is not provided.

---

### F.8.1 The Package TEXT\_IO

The package TEXT\_IO conforms to the specification given in the *Reference Manual for the Ada Programming Language*. String input-output is implemented as defined. File input-output is supported to STANDARD\_INPUT and STANDARD\_OUTPUT only. The possible exceptions that are raised by package TEXT\_IO are as follows:

Exception	When Raised
STATUS_ERROR	Raised by an attempt to operate upon or close a file that is not open (no files can be opened).
NAME_ERROR	Raised if a file name is given with a call of CREATE or OPEN.
MODE_ERROR	Raised by an attempt to read from, or test for the end of, STANDARD_OUTPUT, or to write to STANDARD_INPUT.
END_ERROR	Raised by an attempt to read past the end of STANDARD_INPUT.
USE_ERROR	Raised when an unsupported operation is attempted, that would otherwise be legal.

The type COUNT is defined as follows:

```
type COUNT is range 0 .. INTEGER'LAST;
```

The subtype FIELD is defined as follows:

```
type FIELD is INTEGER range 0 .. 255;
```

---

### F.8.2 The Package IO\_EXCEPTIONS

The specification of the package IO\_EXCEPTIONS is the same as that given in the *Reference Manual for the Ada Programming Language*.

---

## F.9 Other Implementation Characteristics

Implementation characteristics associated with the definition of a main program, various numeric ranges, and implementation limits are summarized in the following sections.

---

### F.9.1 Definition of a Main Program

Any library procedure can be used as a main program provided that it has no formal parameters.

---

### F.9.2 Values of Integer Attributes

The ranges of values for integer types declared in package STANDARD are as follows:

SHORT_SHORT_INTEGER	$-2^7 .. 2^7 - 1$	(-128 .. 127)
SHORT_INTEGER	$-2^{15} .. 2^{15} - 1$	(-32768 .. 32767)
INTEGER	$-2^{31} .. 2^{31} - 1$	(-2147483648 .. 2147483647)

For the package TEXT\_IO, the range of values for types COUNT and FIELD are as follows:

COUNT	$0 .. 2^{31} - 1$	(0 .. 2147483647)
FIELD	$0 .. 255$	

---

### F.9.3 Values of Floating-Point Attributes

Floating-point types are described in Section 3.5.7. The representation attributes of floating-point types are summarized in the following table:

	FLOAT	LONG_FLOAT	LONG_LONG_FLOAT
DIGITS	6	15	18
SIZE	32	64	96
MANTISSA	21	51	61
EMAX	84	204	244
EPSILON	$2^{-20}$	$2^{-50}$	$2^{-60}$
SMALL	$2^{-85}$	$2^{-205}$	$2^{-245}$
LARGE	$2^{84} - 2^{63}$	$2^{204} - 2^{153}$	$2^{244} - 2^{183}$
SAFE_EMAX	125	1021	16382
SAFE_SMALL	$2^{-126}$	$2^{-1022}$	$2^{-16383}$
SAFE_LARGE	$2^{125} - 2^{104}$	$2^{1021} - 2^{970}$	$2^{16382} - 2^{16321}$
FIRST	$-(2^{128} - 2^{104})$	$-(2^{1024} - 2^{971})$	$-(2^{16384} - 2^{16320})$
LAST	$2^{128} - 2^{104}$	$2^{1024} - 2^{971}$	$2^{16384} - 2^{16320}$
MACHINE_RADIX	2	2	2
MACHINE_MANTISSA	24	53	64
MACHINE_EMAX	128	1024	16384
MACHINE_EMIN	-125	-1021	-16382
MACHINE_ROUNDS	FALSE	FALSE	FALSE
MACHINE_OVERFLOWS	FALSE	FALSE	FALSE

**F-10** Implementation-Dependent Characteristics

---

#### F.9.4 Attributes of Type DURATION

The values of the significant attributes of type DURATION are as follows:

DURATION'DELTA	1.E-4	( $10^{-4}$ )
DURATION'SMALL	2#1.0#E-14	( $2^{-14}$ )
DURATION'FIRST	-131072.0000	( $-2^{17}$ )
DURATION'LAST	131071.9999	( $2^{17} - \text{'DELTA}$ )

---

#### F.9.5 Implementation Limits

---

Limit	Description
255	Maximum identifier length (number of characters)
255	Maximum number of characters in a source line
$2^{10}$	Maximum number of library units and subunits in a compilation closure <sup>1</sup>
$2^{12}$	Maximum number of library units and subunits in an execution closure <sup>2</sup>
$2^{16} - 1$	Maximum number of enumeration literals in an enumeration type definition
$2^{16} - 1$	Maximum number of lines in a source file
$2^{31} - 1$	Maximum number of bits in any object
$2^{16} - 1$	Maximum number of exceptions

---

<sup>1</sup>The compilation closure of a given unit is the total set of units that the given unit depends on, directly and indirectly.

<sup>2</sup>The execution closure of a given unit is the compilation closure plus all associated secondary units.

---



---

**LINK**

Creates an executable image file for the specified units.

---

**Format**    **LINK** *unit-name* [*file-spec*,...]  
               **LINK/NOMAIN** *unit-name*[...] *file-spec*[...]

Command Qualifiers	Defaults
/AFTER = time	/AFTER = TODAY
/BATCH_LOG = file-spec	See text.
/BRIEF	See text.
/COMMAND[ = file-spec]	See text.
/[NO]DEBUG[ = file-spec]	/NODEBUG
/ELABORATION = file-spec	See text.
/FULL	See text.
/[NO]IMAGE[ = file-spec]	/IMAGE
/[NO]KEEP	/KEEP
/[NO]LOG	/NOLOG
/[NO]MAIN	/MAIN
/[NO]MAP[ = file-spec]	/NOMAP
/NAME = job-name	See text.
/[NO]NOTIFY	/NOTIFY
/OUTPUT = file-spec	/OUTPUT = SYS\$OUTPUT
/[NO]PRINTER[ = queue-name]	/NOPRINTER
/QUEUE = queue-name	/QUEUE = SYS\$BATCH
/SUBMIT	/WAIT
/WAIT	/WAIT

Parameter Qualifiers	Defaults
/LIBRARY	See text.
/MAPPING	See text.
/TARGET	See text.

# LINK

---

## Prompts

\_Unit:

\_File:

---

## Command Parameters

### *unit-name*

By default (or if you specify the /MAIN qualifier):

- You can specify only one unit, the source code of which must be written in XD Ada.
- The parameter *unit-name* specifies the XD Ada main program, which must be a procedure or function with no parameters. If the main program is a function, it must return a value of a discrete type; the function value is used as the VMS image exit value.

If you specify the /NOMAIN qualifier:

- You can specify one or more foreign units that are to be included in the executable image. The unit names may include percent signs (%) and asterisks (\*) as wildcard characters. (See the <REFERENCE> (VMS\_DCL\_CONCEPTS) for detailed information on wildcard characters.)
- The image transfer address comes from one of the foreign files specified.

### *file-spec*

Specifies a list of object files, object libraries, mapping definition files, and target definition files, that are to be used in linking the program. The default directory is the current default directory. The default file type is .XOB, unless the /LIBRARY, /MAPPING, or /TARGET qualifier is used. No wildcard characters are allowed in a file specification.

If the file is an object library or shareable image library, you must use the /LIBRARY qualifier. The default file type is .XLB.

If the file is a mapping definition file, you must use the /MAPPING qualifier. The default file type is .MPD.

If the file is a target definition file you must use the /TARGET qualifier. The default file type is .TGD.

If you specify the /NOMAIN qualifier, the image transfer address comes from one of the files (not units) specified.

---

## Description

The LINK command performs the following steps:

1. Runs the prebuild phase to generate an elaboration list.
2. Checks if a pragma LINK\_OPTION is specified for the main program, and if specified, verifies that the designated link option name is available in the current program library. If available, the copied link option files in the library corresponding to the link option are used, unless overridden by the /TARGET or /MAPPING qualifiers.

Note that, unlike the CHECK command, the pragma LINK\_OPTION association for units other than the main program unit is not checked.

If no target link option is given for the main program unit or the designated target link option is not found in the library, and the logical symbol XDADA\$TARGET\_DEF is not defined, and a /TARGET qualifier is not specified on the LINK command line, an error is issued. If no mapping link option is given for the main program unit or the designated mapping link option is not found in the library, and the logical symbol XDADA\$MAPPING\_DEF is not defined, and a /MAPPING qualifier is not specified on the XDACS LINK command line, the default mapping in the target definition file is used.

3. If LINK/NOMAIN is not specified, checks that only one unit is specified and that it is an XD Ada main program.
4. Forms the closure of the main program (LINK/MAIN) or of the specified units (LINK/NOMAIN) and verifies that all units in the closure are present, current and complete. If XDACS detects an error, the operation is terminated at the end of the prebuild phase.
5. Creates a DCL command file for the builder. The command file is deleted after the LINK operation is completed or terminated, unless LINK/COMMAND is specified. If LINK/COMMAND is specified, the command file is retained for future use, and the build phase is not carried out.

## LINK

6. Unless the /COMMAND qualifier is specified, performs the build phase as follows:
  - a. By default (LINK/WAIT), the command file generated in step 4 is executed in a subprocess. You must wait for the build operation to terminate before issuing another command. Note that when you specify the /WAIT qualifier (the default), process logical names are propagated to the subprocess generated to execute the command file.
  - b. If you specify the /SUBMIT qualifier, the builder command file is submitted as a batch job.
7. If the /DEBUG qualifier is included in the command line the debug symbol table information is placed in a file with a default file type of .XDS.
8. Creates a loadable output file with a default file type of .RLD.

XDACS output originating before the builder is invoked is reported to your terminal by default, or to a file specified with the /OUTPUT qualifier. Diagnostics are reported to your terminal, by default, or to a log file if the LINK command is executed in batch mode (XDACS LINK/SUBMIT).

See <REFERENCE>(target), <REFERENCE>(map), and <REFERENCE>(build) for more information on the XD Ada target-specific builder commands.

---

## Command Qualifiers

### **/AFTER = time**

Requests that the batch job be held until after a specific time, when the LINK command is executed in batch mode (LINK/SUBMIT). If the specified time has already passed, the job is queued for immediate processing.

You can specify either an absolute time or a combination of absolute and delta time. See the <REFERENCE>(VMS\_DCL\_CONCEPTS) (or type HELP Specify Date-Time at the DCL prompt) for complete information on specifying time values.

### **/BATCH\_LOG = file-spec**

Provides a file specification for the batch log file when the LINK command is executed in batch mode (LINK/SUBMIT).

If you do not give a directory specification with the *file-spec* option, the batch log file is created by default in the current default directory. If you do not give a file specification, the default file name is the job name specified with the */NAME=job-name* qualifier. If no job name has been specified, the program library manager creates a file name comprising up to the first 39 characters of the first unit name specified. If you specified *LINK/NOMAIN* and no job name and there is a wildcard character in the first unit specified, the program library manager uses the default file name *XDACS\_LINK*. The default file type is *.LOG*.

### ***/BRIEF***

Directs the builder to produce a brief image map file. The */BRIEF* qualifier is valid only if you also specify the */MAP* qualifier with the *LINK* command. The */BRIEF* qualifier is incompatible with the */FULL* qualifier.

A brief image map file contains only the following sections:

- Object module information
- Segment mapping information
- Link run statistics

See also the description of the */FULL* qualifier.

### ***/COMMAND[=file-spec]***

Controls whether the builder is invoked as a result of the *LINK* command, and determines whether the command file generated to invoke the builder is saved. If you specify the */COMMAND* qualifier, *XDACS* does not invoke the builder, and the generated command file is saved for you to invoke or submit as a batch job.

The *file-spec* option allows you to enter a file specification for the generated command file. The default directory for the command file is the current default directory. By default, *XDACS* provides a file name comprising up to the first 39 characters of the first unit name specified. If you specified *LINK/NOMAIN* and you used a wildcard character in the first name unit specified, the program library manager uses the default file name *XDACS\_LINK*. The default file type is *.COM*. No wildcard characters are allowed in the file specification.

By default, if the */COMMAND* qualifier is not specified, *XDACS* deletes the generated command file when the *LINK* command completes normally or is terminated.

## LINK

**/DEBUG[ = file-spec]**

**/NODEBUG (D)**

Controls whether a debugger symbol table is created along with the loadable image file.

By default, no debugger symbol table is created.

**/ELABORATION = file-spec**

Provides a file specification for the object file generated by the LINK command. The file is retained by XDACS only when the /COMMAND qualifier is used: that is, when the result of the LINK operation is to produce a builder command file for future use, rather than to invoke the builder immediately.

The generated object file contains the code that directs the elaboration of library packages in the closure of the units specified. Unless you also specify the /NOMAIN qualifier, the object file also contains the image transfer address.

The default directory for the generated object file is the current default directory. The default file type is .XOB. No wildcard characters are allowed in the file specification.

By default, if you do not specify the /ELABORATION qualifier, XDACS provides a file name comprising up to the first 39 characters of the first unit name specified.

By default, if you do not specify the /COMMAND qualifier, XDACS deletes the generated object file when the LINK command completes normally or is terminated.

**/FULL**

Directs the builder to produce a full image map file, which is the most complete image map. The /FULL qualifier is valid only if you also specify the /MAP qualifier with the LINK command. Also, the /FULL qualifier is incompatible with the /BRIEF qualifier.

A full image map file contains the following sections:

- Object module information
- Segment mapping information
- Symbol address information
- Exception numbers
- Link run statistics

**//IMAGE[ =file-spec] (D)**

**/NOIMAGE**

Controls whether the LINK command creates a loadable image file and optionally provides a file specification for the file. The default file type is .RLD. No wildcard characters are allowed in the file specification.

By default, an executable image file is created with a file name comprising up to the first 39 characters of the first unit name specified.

**/KEEP (D)**

**/NOKEEP**

Controls whether the batch log file generated is deleted after it is printed when the LINK command is executed in batch mode (LINK/SUBMIT).

By default, the log file is not deleted.

**/LOG**

**/NOLOG (D)**

Controls whether a list of all the units included in the executable image is displayed. The display shows the units according to the order of elaboration for the program.

By default, a list of all the units included in the executable image is not displayed.

**/MAIN (D)**

**/NOMAIN**

Controls where the image transfer address is to be found.

The /MAIN qualifier indicates that the XD Ada unit specified determines the image transfer address, and hence is to be a main program.

The /NOMAIN qualifier indicates that the image transfer address comes from one of the files specified, and not from one of the XD Ada units specified.

By default (/MAIN), only one XD Ada unit can be specified, and that unit must be an XD Ada main program.

**/MAP[ =file-spec]**

**/NOMAP (D)**

Controls whether the builder creates an image map file and optionally provides a file specification for the file. The default directory for the image map file is the current directory. The default file name comprises up to the first 39 characters of the first unit name specified.

## LINK

The default file type is .MAP. No wildcard characters are allowed in the file specification.

If neither the /BRIEF nor the /FULL qualifier is specified with the /MAP qualifier, /BRIEF is assumed.

By default, no image map file is created.

### **/NAME = job-name**

Specifies a string to be used as the job name and as the file name for the batch log file when the LINK command is executed in batch mode (LINK/SUBMIT). The job name can have from 1 to 39 characters.

By default, if you do not specify the /NAME qualifier, XDACS creates a job name comprising up to the first 39 characters of the first unit name specified. If you specify LINK/NOMAIN but do not specify the /NAME qualifier, and you use a wildcard character in the first unit name specified, the program library manager uses the default file name XDACS\_LINK. In these cases, the job name is also the file name of the batch log file.

### **/NOTIFY (D)**

#### **/NONOTIFY**

Controls whether a message is broadcast when the LINK command is executed in batch mode (LINK/SUBMIT). The message is broadcast to any terminal at which you are logged in, notifying you that your job has been completed or terminated.

By default, a message is broadcast.

### **/OUTPUT = file-spec**

Requests that any output generated before the builder is invoked be written to the file specified rather than to SYS\$OUTPUT. Any diagnostic messages are written to both SYS\$OUTPUT and the file.

The default directory is the current default directory. If you specify a file type but omit the file name, the default file name is XDACS. The default file type is .LIS. No wildcard characters are allowed in the file specification.

By default, the LINK command output is written to SYS\$OUTPUT.



**/PRINTER[=queue-name]****/NOPRINTER (D)**

Controls whether the log file is queued for printing when the LINK command is executed in batch mode (LINK/SUBMIT) and the batch job is completed.

The /PRINTER qualifier allows you to specify a particular print queue. The default print queue for the log file is SYS\$PRINT.

By default, the log file is not queued for printing. If you specify /NOPRINTER, /KEEP is assumed.

**/QUEUE = queue-name**

Specifies the batch job queue in which the job is entered when the LINK command is executed in batch mode (LINK/SUBMIT).

By default, if the /QUEUE qualifier is not specified, the job is placed in the default system batch job queue, SYS\$BATCH.

**/SUBMIT**

Directs XDACS to submit the command file generated for the builder to a batch queue. You can continue to issue commands in your current process without waiting for the batch job to complete. The builder output is written to a batch log file.

By default, the generated command file is executed in a subprocess (LINK/WAIT).

**/WAIT**

Directs XDACS to execute the command file generated for the builder in a subprocess. Execution of your current process is suspended until the subprocess completes. The builder output is written directly to your terminal. Note that process logical names are propagated to the subprocess generated to execute the command file.

By default, XDACS executes the command file generated for the builder in a subprocess: you must wait for the subprocess to terminate before you can issue another command.

---

## Parameter Qualifiers

**/LIBRARY**

Indicates that the associated input file is an object module library to be searched for modules to resolve any undefined symbols in the input files. The default file type is .XLB.

## LINK

By default, if you do not specify the /LIBRARY qualifier, the file is assumed to be an object file with a default file type of .XOB.

### /MAPPING

Indicates that the associated input file is a mapping definition file. Mapping definition files control the location of the program on the target system. The default file type is .MPD.

By default, if you do not specify the /MAPPING qualifier, the file is assumed to be an object file with a default file type of .XOB.

### /TARGET

Indicates that the associated input file is a target definition file. Target definition files describe the target system's memory. The default file type is .TGD.

By default, if you do not specify the /TARGET qualifier, the file is assumed to be an object file with a default file type of .XOB.

---

## Examples

1. XDACS> LINK CONTROL\_LOOP

%ACS-I-CL\_LINKING, Invoking the XD Ada Builder

The LINK command forms the closure of the unit CONTROL\_LOOP, which is an XD Ada main program, creates a builder command file and package elaboration file, then invokes the command file in a spawned subprocess.

2. XDACS> LINK/SUBMIT CONTROL\_LOOP LOOP\_FUNCTIONS/LIBRARY

%ACS-I-CL\_SUBMITTED, Job CONTROL\_LOOP (queue ALL\_BATCH, entry 134)  
started on FAST\_BATCH

The LINK command instructs the builder to link the closure of the XD Ada main program CONTROL\_LOOP against the library LOOP\_FUNCTIONS.XLB. The /SUBMIT qualifier causes XDACS to submit the builder command file as a batch job.

3. ADATS> LINK/NOMAIN FLUID\_VOLUME, COUNTER MONITOR.XOB  
%ACS-I-OL\_LINKING, Invoking the XD Ada Builder

The LINK command builds all the XD Ada units FLUID\_VOLUME and COUNTER with the foreign object file MONITOR.XOB. The /NOMAIN qualifier tells the builder that the image transfer address is in the foreign file.

## XDADA

---

## XDADA

Invokes the XD Ada compiler to compile one or more source files.

---

### Format **XDADA** *file-spec[,...]*

#### Command Qualifiers

/LIBRARY = directory-spec

#### Defaults

/LIBRARY = XDADA\$LIB

#### Positional Qualifiers

/[NO]ANALYSIS\_DATA[ = file-spec]

/[NO]CHECK

/[NO]COPY\_SOURCE

/[NO]DEBUG[ = (option[,...])]

/[NO]DIAGNOSTICS[ = file-spec]

/[NO]ERROR\_LIMIT[ = n]

/[NO]LIST[ = file-spec]

/[NO]LOAD[ = option]

/[NO]MACHINE\_CODE

/[NO]NOTE\_SOURCE

/[NO]OPTIMIZE[ = (option[,...])]

/[NO]PREDEFINED\_UNIT

/[NO]SHOW[ = option]

/[NO]SYNTAX\_ONLY

/[NO]WARNINGS[ = (option[,...])]

#### Defaults

/NOANALYSIS\_DATA

See text.

/COPY\_SOURCE

/DEBUG = ALL

/NODIAGNOSTICS

/ERROR\_LIMIT = 30

/NOLIST

/LOAD = REPLACE

/NOMACHINE\_CODE

/NOTE\_SOURCE

See text.

/NOPREDEFINED\_UNIT

/SHOW = PORTABILITY

/NOSYNTAX\_ONLY

See text.

---

### Prompt

\_File:

---

### Command Parameters

#### *file-spec*

Specifies one or more XD Ada source files to be compiled. If you do not specify a file type, the compiler uses the default file type of .ADA. No wildcard characters are allowed in the file specifications.

If you specify several source files as arguments to the XDADA command, you must separate adjacent file specifications with a comma (,). If you specify more than one input file, you must separate adjacent file specifications with a comma (,). You cannot use a plus sign (+) to separate file specifications.

---

## Description

The XDADA command is one of three commands used to compile compilation units. The other two are the XDACS COMPILE and RECOMPILE commands. All three commands invoke the XD Ada cross-compiler for the <REFERENCE>(proc).

The XDADA command can be used at any time to compile one or more source files (.ADA); it must be used to compile units into a library for the first time or to compile again a set of units where the order of compilation has changed.

XD Ada source files are compiled in the order in which they appear on the command line. If a source file contains more than one XD Ada compilation unit, the units are compiled in the order in which they appear in the source file. The Ada rules governing the order in which compilation units are compiled are summarized in Version 2.0 of <REFERENCE>(dap).

The XDADA command compiles units in the context of the current program library. Whenever a compilation unit is successfully compiled, the current program library is updated as follows:

- An object file (.XOB), which contains the object module, is usually created in the library.
- A compilation unit file (.ACU) is always created in the library.
- Unless suppressed by the /NOCOPY\_SOURCE qualifier on the XDADA command, the file specification of the XD Ada source file is noted in the library.
- The library index file is revised.
- If the unit was previously compiled into the program library, the obsolete versions of the associated library files are deleted.

See <REFERENCE>(prg\_lib\_mgr) and Version 2.0 of <REFERENCE>(dap) for more information on program libraries, sublibraries, and compilation.

---

## Command Qualifiers

### ***/LIBRARY = directory-spec***

Specifies the program library that is to be the current program library for the duration of the compilation. The directory specified must be an already existing XD Ada program library. No wildcard characters are allowed in the directory specification.

By default, the current program library is the program library last specified in a SET LIBRARY command. The logical name XDADA\$LIB is assigned to the program library specified in a SET LIBRARY command.

---

## Positional Qualifiers

### ***/ANALYSIS\_DATA[ = file-spec]***

#### ***/NOANALYSIS\_DATA (D)***

Controls whether a data analysis file containing source code cross-reference and static analysis information is created. The data analysis file is supported only for use with DIGITAL layered products, such as the VAX Source Code Analyzer.

One data analysis file is created for each source file compiled. The default directory for data analysis files is the current default directory. The default file name is the name of the source file being compiled. The default file type is .ANA. No wildcard characters are allowed in the file specification.

By default, no data analysis file is created.

### ***/CHECK***

#### ***/NOCHECK***

Controls whether all run-time checks are suppressed. The /NOCHECK qualifier is equivalent to having all possible SUPPRESS pragmas in the source code.

Explicit use of the /CHECK qualifier overrides any occurrences of the pragmas SUPPRESS and SUPPRESS\_ALL in the source code, without the need to edit the source code.

By default, run-time checks are suppressed only in cases where a pragma SUPPRESS or SUPPRESS\_ALL appears in the source.

See the <REFERENCE>(xlrn) for more information on the pragmas SUPPRESS and SUPPRESS\_ALL.

**/COPY\_SOURCE (D)****/NOCOPY\_SOURCE**

Controls whether a copied source file (.ADC) is created in the current program library when a compilation unit is compiled without error. The RECOMPILE command (and thus the COMPILE command) requires that a copied source file exist in the current program library for any unit that is to be recompiled.

By default, a copied source file is created in the current program library when a unit is compiled without error.

**/DEBUG[=(option[...])] (D)****/NODEBUG**

Controls which compiler debugging options are provided. You can debug XD Ada programs with the XD Ada Debugger (see <REFERENCE>(debug\_ch)). You can request the following options:

ALL	Provides both SYMBOLS and TRACEBACK.
NONE	Provides neither SYMBOLS nor TRACEBACK.
[NO]SYMBOLS	Controls whether debugger symbol records are included in the object file.
[NO]TRACEBACK	Controls whether traceback information (a subset of the debugger symbol information) is included in the object file.

By default, both debugger symbol records and traceback information are included in the object file (/DEBUG=ALL, or equivalently: /DEBUG).

**/DIAGNOSTICS[=file-spec]****/NODIAGNOSTICS (D)**

Controls whether a diagnostics file containing compiler messages and diagnostic information is created. The diagnostics file is supported only for use with DIGITAL layered products, such as the VAX Language-Sensitive Editor.

One diagnostics file is created for each source file compiled. The default directory for diagnostics files is the current default directory. The default file name is the name of the source file being compiled. The default file type is .DIA. No wildcard characters are allowed in the file specification.

By default, no diagnostics file is created.

**/ERROR\_LIMIT[=n]****NOERROR\_LIMIT**

Controls whether execution of the XDADA command for a given compilation unit is terminated upon the occurrence of the nth E-level error within that unit.

Error counts are not accumulated across a sequence of compilation units. If the /ERROR\_LIMIT=n option is specified, each compilation unit may have up to n-1 errors without terminating the compilation. When the error limit is reached within a compilation unit, compilation of that unit is terminated, but compilation of subsequent units continues.

The /ERROR\_LIMIT=0 option is equivalent to /ERROR\_LIMIT=1.

By default, execution of the XDADA command is terminated for a given compilation unit upon the occurrence of the 30th E-level error within that unit (equivalent to /ERROR\_LIMIT=30).

**/LIST[=file-spec]****/NOLIST (D)**

Controls whether a listing file is created. One listing file is created for each source file compiled. The default directory for listing files is the current default directory. The default file name is the name of the source file being compiled. The default file type is .LIS. No wildcard characters are allowed in the file specification.

By default, the XDADA command does not create a listing file.

**/LOAD[=option]****/NOLOAD****LOAD=REPLACE (D)**

Controls whether the current program library is updated with the successfully processed units contained in the specified source files. Depending on other qualifiers specified (or not specified) with the ADA command, processing can involve full compilation, syntax checking only, and so on. The /NOLOAD qualifier causes the units in the specified source files to be processed, but prevents the current program library from being updated.



You can specify the following option:

**[NO]REPLACE**

Controls whether a unit added to the current program library replaces an existing unit with the same name. If you specify the **NOREPLACE** option, the unit is added to the current program library only if no existing unit has the same name, except if the new unit is the corresponding body of an existing specification or vice versa.

By default, the current program library is updated with the successfully processed units, and a unit added to the current program library replaces an existing unit with the same name.

**/MACHINE\_CODE**

**/NOMACHINE\_CODE (D)**

Controls whether generated machine code (approximating assembly language notation) is included in the listing file.

By default, generated machine code is not included in the listing file.

**/NOTE\_SOURCE (D)**

**/NONOTE\_SOURCE**

Controls whether the file specification of the source file is noted in the program library when a unit is compiled without error. The **COMPILE** command uses this information to locate revised source files.

By default, the file specification of the source file is noted in the program library when a unit is compiled without error.

**/OPTIMIZE[=(option[,...])]**

**/NOOPTIMIZE**

Controls the level of optimization that is applied in producing the compiled code. You can specify one of the following primary options:

<b>TIME</b>	Provides full optimization with time as the primary optimization criterion. Overrides any occurrences of the pragma <b>OPTIMIZE(SPACE)</b> in the source code.
<b>SPACE</b>	Provides full optimization with space as the primary optimization criterion. Overrides any occurrences of the pragma <b>OPTIMIZE(TIME)</b> in the source code.

## XDADA

DEVELOPMENT	Recommended when active development of a program is in progress. Provides some optimization, but development considerations and ease of debugging take preference over optimization. This option overrides pragmas that establish a dependence on a subprogram (the pragma <code>INLINE</code> ), and thus reduces the need for recompilations when such bodies are modified.
NONE	Provides no optimization. Suppresses expansions in line of subprograms, including those specified by the pragma <code>INLINE</code> .

The `/NOOPTIMIZE` qualifier is equivalent to `/OPTIMIZE = NONE`.

By default, the XDADA command applies full optimization with space as the primary optimization criterion (like `/OPTIMIZE = SPACE`, but observing uses of the pragma `OPTIMIZE`).

The `/OPTIMIZE` qualifier also has a set of secondary options that you can use separately or together with the primary options to override the default behavior for expansion in line.

The `INLINE` secondary option can have the following values (see the `<REFERENCE>`(rts) for more information about expansion in line).

INLINE:NONE	Disables subprogram expansion in line. This option overrides any occurrences of the pragma <code>INLINE</code> in the source code, without having to edit the source file. It also disables implicit expansion in line of subprograms. ( <i>Implicit expansion in line</i> means that the compiler assumes a pragma <code>INLINE</code> for certain subprograms as an optimization.) A call to a subprogram in another unit is not expanded in line, regardless of the <code>/OPTIMIZE</code> options in effect when that unit was compiled.
INLINE:NORMAL	Provides normal subprogram expansion in line. Subprograms to which an explicit pragma <code>INLINE</code> applies are expanded in line under certain conditions. In addition, some subprograms are implicitly expanded in line. The compiler assumes a pragma <code>INLINE</code> for calls to some small local subprograms (subprograms that are declared in the same unit as the unit in which the call occurs).

**INLINE:SUBPROGRAMS** Provides maximal subprogram expansion in line.

In addition to the normal subprogram expansion in line that occurs when **INLINE:NORMAL** is specified, this option results in implicit expansion in line of some small subprograms declared in other units. The compiler assumes a pragma **INLINE** for any subprogram if it improves execution speed and reduces code size. This option may establish a dependence on the body of another unit, as would be the case if a pragma **INLINE** were specified explicitly in the source code.

**INLINE:MAXIMAL** Provides maximal subprogram expansion in line. Maximal subprogram expansion in line occurs as for **INLINE:SUBPROGRAMS**.

By default, the **/OPTIMIZE** qualifier primary options have the following secondary-option values:

<b>/OPTIMIZE=TIME</b>	<b>=(INLINE:NORMAL)</b>
<b>/OPTIMIZE=SPACE</b>	<b>=(INLINE:NORMAL)</b>
<b>/OPTIMIZE=DEVELOPMENT</b>	<b>=(INLINE:NONE)</b>
<b>/OPTIMIZE=NONE</b>	<b>=(INLINE:NONE)</b>

See Chapter 3 of Version 2.0 of <REFERENCE>(dap) for a further discussion of the **/OPTIMIZE** qualifier and its options.

#### ***/PREDEFINED\_UNIT***

##### ***/NOPREDEFINED\_UNIT (D)***

Controls the compilation of package **\$RUN\_TIME\_SYSTEM**, package **\$TASKING\_SYSTEM**, and package **MACHINE\_CODE**. You must specify this qualifier in order to be able to compile these packages. The qualifier is not required for the compilation of any other source files. See the <REFERENCE>(rts) for more information.

By default, **/PREDEFINED\_UNIT** is omitted.

## XDADA

**/SHOW[=option] (D)**

**/NOSHOW**

Controls the listing file options included when a listing file is provided. You can specify one of the following options:

ALL	Provides all listing file options.
[NO]PORTABILITY	Controls whether a program portability summary is included in the listing file. By default, the XDADA command provides a portability summary (/SHOW=PORTABILITY). See <REFERENCE>(port_summ) for details of what can be included in a portability summary. See Chapter 5 of Version 2.0 of <REFERENCE>(dap) for more information on program portability.
NONE	Provides none of the listing file options (same as NOSHOW).

By default, the XDADA command provides a portability summary (/SHOW=PORTABILITY).

**/SYNTAX\_ONLY**

**/NOSYNTAX\_ONLY (D)**

Controls whether the source file is to be checked only for correct syntax. If you specify the /SYNTAX\_ONLY qualifier, other compiler checks are not performed (for example, semantic analysis, type checking, and so on), and the program library is not updated.

By default, the compiler performs all checks.

**/WARNINGS[=(message-option[,...])]**

**/NOWARNINGS**

Controls which categories of informational (I-level) and warning (W-level) messages are displayed and where those messages are displayed. You can specify any combination of the following message options:

WARNINGS: (destination[,...])  
NOWARNINGS

WEAK\_WARNINGS: (destination[,...])  
NOWEAK\_WARNINGS

SUPPLEMENTAL: (destination[,...])  
NOSUPPLEMENTAL

COMPILATION\_NOTES: (*destination*[,...])  
 NOCOMPILATION\_NOTES

STATUS: (*destination*[,...])  
 NOSTATUS

The possible values of *destination* are ALL, NONE, or any combination of TERMINAL (terminal device), LISTING (listing file), DIAGNOSTICS (diagnostics file). The message categories are summarized as follows:

WARNINGS	W-level: Indicates a definite problem in a legal program, for example, an unknown pragma.
WEAK_WARNINGS	I-level: Indicates a potential problem in a legal program; for example, a possible CONSTRAINT_ERROR at run time. These are the only kind of I-level messages that are counted in the summary statistics at the end of a compilation.
SUPPLEMENTAL	I-level: Additional information associated with preceding E-level or W-level diagnostics.
COMPILATION_NOTES	I-level: Information about how the compiler translated a program, such as record layout, parameter-passing mechanisms, or decisions made for the pragmas INLINE, INTERFACE, or the import-subprogram pragmas.
STATUS	I-level: End of compilation statistics and other messages.

The defaults are as follows:

```
/WARNINGS=(WARN:ALL,WEAK:ALL,SUPP:ALL,COMP:NONE,STAT:LIST)
```

If you specify only some of the message categories with the /WARNINGS qualifier, the default values for other categories are used.

---

## Examples

1. \$ XDADA MODEL\_INTERFACE\_,MODEL\_INTERFACE,CONTROL\_LOOP

The XDADA command compiles the compilation units contained in the three files MODEL\_INTERFACE\_.ADA, MODEL\_INTERFACE.ADA, and CONTROL\_LOOP.ADA, in the order given.

## XDADA

2. \$ XDADA/LIST/SHOW=ALL SCREEN\_IO\_,SCREEN\_IO

The XDADA command compiles the compilation units contained in the two files SCREEN\_IO\_.ADA and SCREEN\_IO.ADA, in the order given. The /LIST qualifier creates the listing files SCREEN\_IO\_.LIS and SCREEN\_IO.LIS in the current default directory. The /SHOW=ALL qualifier causes all listing file options to be provided in the listing files.

---

APPENDIX C  
TEST PARAMETERS

Certain tests in the ACVC make use of implementation-dependent values, such as the maximum length of an input line and invalid file names. A test that makes use of such values is identified by the extension .TST in its file name. Actual values to be substituted are represented by names that begin with a dollar sign. A value must be substituted for each of these names before the test is run. The values used for this validation are given below:

<u>Name and Meaning</u>	<u>Value</u>
\$ACC_SIZE An integer literal whose value is the number of bits sufficient to hold any value of an access type.	32
\$BIG_ID1 Identifier the size of the maximum input line length with varying last character.	(1..254=>'A', 255=>1)
\$BIG_ID2 Identifier the size of the maximum input line length with varying last character.	(1..254=>'A', 255=>2)
\$BIG_ID3 Identifier the size of the maximum input line length with varying middle character.	(1..127=>'A', 128=>3, 129..255=>'A')
\$BIG_ID4 Identifier the size of the maximum input line length with varying middle character.	(1..127=>'A', 128=>4, 129..255=>'A')
\$BIG_INT_LIT An integer literal of value 298 with enough leading zeroes so that it is the size of the maximum line length	(1..252=>0, 253..255=>298)
\$BIG_REAL_LIT A universal real literal of value 690.0 with enough leading zeroes to be the size of the maximum line length.	(1..249=>0, 250..255=>69.0E1)
\$BIG_STRING1 A string literal which when catenated with BIG_STRING2 yields the image of BIG_ID1.	(1..127=>'A')

## TEST PARAMETERS

---

<b>\$BIG_STRING2</b>	(1..127=>'A', 128=>1)
A string literal which when catenated to the end of BIG_STRING1 yields the image of BIG_ID1.	
<b>\$BLANKS</b>	(1..235=>' ')
A sequence of blanks twenty characters less than the size of the maximum line length.	
<b>\$COUNT_LAST</b>	2147483647
A universal integer literal whose value is TEXT_IO.COUNT'LAST.	
<b>\$DEFAULT_MEM_SIZE</b>	16777216
An integer literal whose value is SYSTEM.MEMORY_SIZE.	
<b>\$DEFAULT_STOR_UNIT</b>	8
An integer literal whose value is SYSTEM.STORAGE_UNIT.	
<b>\$DEFAULT_SYS_NAME</b>	MC68000
The value of the constant SYSTEM.SYSTEM_NAME.	
<b>\$DELTA_DOC</b>	2#1.0#E-31
A real literal whose value is SYSTEM.FINE_DELTA.	
<b>\$FIELD_LAST</b>	255
A universal integer literal whose value is TEXT_IO.FIELD'LAST.	
<b>\$FIXED_NAME</b>	NO_SUCH_TYPE
The name of a predefined fixed-point type other than DURATION.	
<b>\$FLOAT_NAME</b>	LONG_LONG_FLOAT
The name of a predefined floating-point type other than FLOAT, SHORT_FLOAT, or LONG_FLOAT.	
<b>\$GREATER_THAN_DURATION</b>	131072.0
A universal real literal that lies between DURATION'BASE'LAST and DURATION'LAST or any value in the range of DURATION.	
<b>\$GREATER_THAN_DURATION_BASE_LAST</b>	131073.0
A universal real literal that is greater than DURATION'BASE'LAST.	



## TEST PARAMETERS

---

\$HIGH_PRIORITY	15
An integer literal whose value is the upper bound of the range for the subtype SYSTEM.PRIORITY.	
\$ILLEGAL_EXTERNAL_FILE_NAME1	THERE ARE NO ILLEGAL FILENAMES
An external file name which contains invalid characters.	
\$ILLEGAL_EXTERNAL_FILE_NAME2	N/A
An external file name which is too long.	
\$INTEGER_FIRST	-2147483648
A universal integer literal whose value is INTEGER'FIRST.	
\$INTEGER_LAST	2147483647
A universal integer literal whose value is INTEGER'LAST.	
\$INTEGER_LAST_PLUS_1	2147483648
A universal integer literal whose value is INTEGER'LAST+1.	
\$LESS_THAN_DURATION	-131072.0
A universal real literal that lies between DURATION'BASE'FIRST and DURATION'FIRST or any value in the range of DURATION.	
\$LESS_THAN_DURATION_BASE_FIRST	-131073.0
A universal real literal that is less than DURATION'BASE'FIRST.	
\$LOW_PRIORITY	0
An integer literal whose value is the lower bound of the range for the subtype SYSTEM.PRIORITY.	
\$MANTISSA_DOC	31
An integer literal whose value is SYSTEM.MAX_MANTISSA.	
\$MAX_DIGITS	18
Maximum digits supported for floating-point types.	
\$MAX_IN_LEN	255
Maximum input line length permitted by the implementation.	

---

\$MAX_INT	2147483647
A universal integer literal whose value is SYSTEM.MAX_INT.	
\$MAX_INT_PLUS_1	2147483648
A universal integer literal whose value is SYSTEM.MAX_INT+1.	
\$MAX_LEN_INT_BASED_LITERAL	(1..2=>'2:', 3..252=>'0', 253..255=>'11:') A universal integer based literal whose value is 2#11# with enough leading zeroes in the mantissa to be MAX_IN_LEN long.
\$MAX_LEN_REAL_BASED_LITERAL	(1..3=>'16:', 4..251=>'0', 252..255=>'F.E:') A universal real based literal whose value is 16:F.E: with enough leading zeroes in the mantissa to be MAX_IN_LEN long.
\$MAX_STRING_LITERAL	(1=>'"', 2..254=>'A', 255=>'")' A string literal of size MAX_IN_LEN, including the quote characters.
\$MIN_INT	-2147483648
A universal integer literal whose value is SYSTEM.MIN_INT.	
\$MIN_TASK_SIZE	32
An integer literal whose value is the number of bits required to hold a task object which has no entries, no declarations, and "NULL;" as the only statement in its body.	
\$NAME	SHORT_SHORT_INTEGER
A name of a predefined numeric type other than FLOAT, INTEGER, SHORT_FLOAT, SHORT_INTEGER, LONG_FLOAT, or LONG_INTEGER.	
\$NAME_LIST	MC68000
A list of enumeration literals in the type SYSTEM.NAME, separated by commas.	
\$NEG_BASED_INT	16#FFFF_FFFF#
A based integer literal whose highest order nonzero bit falls in the sign bit position of the representation for SYSTEM.MAX_INT.	

## TEST PARAMETERS

---

<b>\$NEW_MEM_SIZE</b>	123456
An integer literal whose value is a permitted argument for pragma memory_size, other than \$DEFAULT_MEM_SIZE. If there is no other value, then use \$DEFAULT_MEM_SIZE.	
<b>\$NEW_STOR_UNIT</b>	8
An integer literal whose value is a permitted argument for pragma storage_unit, other than \$DEFAULT_STOR_UNIT. If there is no other permitted value, then use value of SYSTEM.STORAGE_UNIT.	
<b>\$NEW_SYS_NAME</b>	MC68000
A value of the type SYSTEM.NAME, other than \$DEFAULT_SYS_NAME. If there is only one value of that type, then use that value.	
<b>\$TASK_SIZE</b>	32
An integer literal whose value is the number of bits required to hold a task object which has a single entry with one inout parameter.	
<b>\$TICK</b>	2#1.0#E-13
A real literal whose value is SYSTEM.TICK.	

## APPENDIX D

## WITHDRAWN TESTS

Some tests are withdrawn from the ACVC because they do not conform to the Ada Standard. The following 44 tests had been withdrawn at the time of validation testing for the reasons indicated. A reference of the form AI-ddddd is to an Ada Commentary.

- E28005C      This test expects that the string "-- TOP OF PAGE. --63" of line 204 will appear at the top of the listing page due to a pragma PAGE in line 203; but line 203 contains text that follows the pragma, and it is this that must appear at the top of the page.
- A39005G      This test unreasonably expects a component clause to pack an array component into a minimum size (line 30).
- B97102E      This test contains an unintended illegality: a select statement contains a null statement at the place of a selective wait alternative (line 31).
- C97116A      This test contains race conditions, and it assumes that guards are evaluated indivisibly. A conforming implementation may use interleaved execution in such a way that the evaluation of the guards at lines 50 & 54 and the execution of task CHANGING\_OF\_THE\_GUARD results in a call to REPORT.FAILED at one of lines 52 or 56.
- BC3009B      This test wrongly expects that circular instantiations will be detected in several compilation units even though none of the units is illegal with respect to the units it depends on; by AI-00256, the illegality need not be detected until execution is attempted (line 95).
- CD2A62D      This test wrongly requires that an array object's size be no greater than 10 although its subtype's size was specified to be 40 (line 137).
- CD2A63A..D, CD2A66A..D, CD2A73A..D, CD2A76A..D [16 tests]  
These tests wrongly attempt to check the size of objects of a derived type (for which a 'SIZE length clause is given) by passing them to a derived subprogram (which implicitly converts them to the parent type (Ada standard 3.4:14)). Additionally, they use the 'SIZE length clause and attribute, whose interpretation is considered problematic by the WG9 ARG.
- CD2A81G, CD2A83G, CD2A84N & M, & CD5011O [5 tests]  
These tests assume that dependent tasks will terminate while the main program executes a loop that simply tests for task termination; this is not the case, and the main program may loop indefinitely (lines 74, 85, 86 & 96, 86 & 96, and 58, resp.).

---

CD2B15C & CD7205C

These tests expect that a 'STORAGE\_SIZE length clause provides precise control over the number of designated objects in a collection; the Ada standard 13.2:15 allows that such control must not be expected.

CD2D11B

This test gives a SMALL representation clause for a derived fixed-point type (at line 30) that defines a set of model numbers that are not necessarily represented in the parent type; by Commentary AI-00099, all model numbers of a derived fixed-point type must be representable values of the parent type.

CD5007B

This test wrongly expects an implicitly declared subprogram to be at the the address that is specified for an unrelated subprogram (line 303).

ED7004B, ED7005C & D, ED7006C & D [5 tests]

These tests check various aspects of the use of the three SYSTEM pragmas; the AVO withdraws these tests as being inappropriate for validation.

CD7105A

This test requires that successive calls to CALENDAR.CLOCK change by at least SYSTEM.TICK; however, by Commentary AI-00201, it is only the expected frequency of change that must be at least SYSTEM.TICK--particular instances of change may be less (line 29).

CD7203B, & CD7204B

These tests use the 'SIZE length clause and attribute, whose interpretation is considered problematic by the WG9 ARG.

CD7205D

This test checks an invalid test objective: it treats the specification of storage to be reserved for a task's activation as though it were like the specification of storage for a collection.

CE2107I

This test requires that objects of two similar scalar types be distinguished when read from a file--DATA\_ERROR is expected to be raised by an attempt to read one object as of the other type. However, it is not clear exactly how the Ada standard 14.2.4:4 is to be interpreted; thus, this test objective is not considered valid. (line 90)

CE3111C

This test requires certain behavior, when two files are associated with the same external file, that is not required by the Ada standard.

CE3301A

This test contains several calls to END\_OF\_LINE & END\_OF\_PAGE that have no parameter: these calls were intended to specify a file, not to refer to STANDARD\_INPUT (lines 103, 107, 118, 132, & 136).

CE3411B

This test requires that a text file's column number be set to COUNT'LAST in order to check that LAYOUT\_ERROR is raised by a subsequent PUT operation. But the former operation will generally raise an exception due to a lack of available disk space, and the test would thus encumber validation testing.

## N C C V S R A D D E N D U M

This Addendum to the ACVC 1.10 VSR clarifies some items which are contained within the standard pre-forma Validation Summary Report as supplied by the Ada Maintenance Office (AMO).

In line with AJPO regulations the contents of the VSR have not been altered in order to keep consistency between the different AVF's.

The points raised in this addendum are being addressed by the AMO in future issues of the VSR.

- 1     The last paragraph of Chapter 1 contains the following statement 'Any test that was determined to contain an illegal language construct or an erroneous language construct is withdrawn from the ACVC...'

This is incorrect since illegal constructs are legitimately contained within Class B tests.

- 2     Both the terms 'inapplicable' and 'not applicable' are used within the VSR. These terms are identical.

- 3     Chapter 1 of the VSR does not indicate how 'inapplicable' tests are to be analysed. The analysis is undertaken as follows:

'Each inapplicable test is checked to ensure that this behaviour is consistent with the given reasons for its inapplicability'.